

Calibration Certificate

Al Takamul Yard, North Rumailah Iraq

• Phone : +964 7810009138 • www.qualitycontrol-iraq • E-mail: op@qualitycontrol-iraq

Date of Issue: September 22, 2026

Page 1 of 1

REQUEST NUMBER	By Contract	APPROVED BY LAB INCHARGE QC
QC JOB NUMBER	QC-CAL-26154	
CERTIFICATE NUMBER	QC-CAL-26154-09	

CUSTOMER DETAILS

Name : **Egyptian Maintenance Company(EMC) IRAQ**
 Address : Basra , South Iraq



EQUIPMENT IDENTIFICATION AND SPECIFICATIONS

Description : **Torque Wrench**
 Type of Indication : Analog
 Manufacturer : NA
 Model : NA
 Serial Number : **2009003**
Calibrated Range : 300 to 750 N.m
 Resolution : 25 N.m
 Tolerance : $\pm 4 \%$
 As Found : In Tolerance
 Calibration Date : September 22, 2026
 Calibration Due : **September 21, 2027**



ENVIRONMENTAL CONDITIONS DURING TEST

Ambient Temperature : 40 °C $\pm$ 5°C Relative Humidity : 25 %RH $\pm$ 5% RH

CALIBRATION METHOD

This calibration was carried out in compliance with ISO/IEC 17025, 2017 & ISO 9001, 2015, With ISO 6789-1&2 Standards.

Verify the torque wrench at minimum 3 points, 20%, 60% and 100% of its maximum torque capacity. Calibrate or replace if verification is not within manufacturer's specifications.

REFERENCE EQUIPMENT USED :

DESCRIPTION	MAKE / MODEL	SERIAL #	CALIBRATION DATE	CALIBRATION DUE DATE
Torque Wrench Calibrator	Nobar / Pro Test 1500	90962	November 3, 2025	November 2, 2026

CALIBRATION TEST RESULTS

Measurement Data For Torque

Clockwise Measurements

Readings on UUC	Readings on Ref. Standard (Avg. of 5 Measurements)	Deviation	Error Percentage (Tolerance $\pm 4\%$)	Uncertainty (95 % C.L.)
N.m	N.m	N.m	%	$\pm$ N.m
300.0	301.0	-1.00	-0.3	12.00
500.0	501.5	-1.50	-0.3	20.00
750.0	753.0	-3.00	-0.4	30.00

Counter Clockwise Measurements

300.0	300.5	-0.50	-0.2	12.00
500.0	501.2	-1.20	-0.2	20.00
750.0	752.0	-2.00	-0.3	30.00

Calibration results were found to conform as per specified accuracy requirements. Above Instrument has **PASSED** its Calibration.

The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor $k=2$, providing a level of confidence of approximately 95%. The uncertainty evaluation has been carried out in accordance with international practice.

DEVIATION FROM STANDARD METHOD : None

REMARK (S) : ☒ The results are as found (no adjustment done).
☐ The results are post adjustment.