



CERTIFICATE OF INSPECTION AFTER REPAIR FOR BIT. SUB

Client Name:	HILONG OIL SERVICES & ENGINEERING CO.LTD	Report No.:	QC-02-24-0034-001
Acceptance Criteria.	<input checked="" type="checkbox"/> API SPEC 7-2	Date Of Inspection:	24-02-2024
Work Location:	ABERDEEN WORK SHOP BASRA IRAQ	Rig Name	HL 22
TEST EQUIPMENT & CONSUMABLE DETAILS			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN,2025	TECHNICAL DETAILS	Wet Visible Continuous
BLACK INK 7HF	Batch#: 220605 Manufacture: Magnaflux Exp Date: JULY,2025	COIL(1200 AMP-TURNS/IN	SC 22713 Cal.14.FEB.2024 Cal Due15.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March,2025	A.C HAND YOKE	201504053 Cal. 14.FEB.2024 Cal Due15.AUG.2024
INTENSITY METER	SR# R.043943 Cal.14.FEB.2024 Cal Due 15.AUG.2024	UV BLACK LIGHT	SR#1900084 Cal. 14.FEB.2024 Cal Due15.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 CAL.Date. 14.FEB.2024 CAL Due Date 15.AUG.2024	THREAD PROFILE GAGE	SR#21336 CAL.Date. 14.FEB.2024 CAL Due Date. 15.AUG.2024 SR#21335 CAL.Date. 14.FEB.2024 CAL Due Date. 15.AUG.2024
Magnetic Partical Concentration 7 HF	1.2 TO 2.4 ML/100 ML	WMPT Light Intensity	3520 Lux
Magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	UV LIGHT INTENSITY:	2950 μw/cm ²
Magnituum Direction (Longitudenal)			
METHODOLOGY:	• Through Visual inspection • MPI inspection with Ultraviolet light • Dimensional *Lead Gaiging, Taper Gauging & Thread Profile Gauging.		

Serial No.	Description	Connection		Result Inspection			Dimensional 3 Inspection															
		Box		Box	Box	Body	Box					Box				Body						
		Box	Box				OD(In)	CB φ(In)	CB δ(In)	BBD φ(In)	BBL δ(In)	Bevel φ(In)	OD(In)	CB φ(In)	CB δ(In)	FBD φ(In)	FBL δ(In)	Bevel φ(In)	Flaring	Nick (In)	Overall λ (In)	Tong Box
7766	BIT SUB	NC 50	----	Acc	----	----	7"	5 5/16"	5/8"	----	----	6 1/2"	----	----	----	----	----	----	----	----	15 3/4"	----

Conclusion :	*01 BIT SUB Was Found "Acceptable" from Box Side Connection at time of Inspection.After Repair.
---------------------	---

Abbreviations :

OD	Outside Diameter	ID	Inside Diameter	SRG	Stress Relief Groove	CB	Counter Bore	BB	Bore Back	FB	Float Bore
Φ	Diameter	λ	Length	ϖ	Width	δ	Depth	NP.	Not Present	NA.	Not Applicable
EGR	Elevator Groove Recess	SGR	Slip Groove Recess	CR	Crack	B	Bent	PC	Premium Class	RF	Reface
GT	Galled Thread	TP	Thread Pitting	SP	Seal Pitting	TD	Thread Damage	SD	Seal Damage	M	Mashed
1	100 % Coating	2	99-71 % Coating	3	70-40 % Coating	4	Up to 40 %	5	Nil	WT	Wall Thickness
Colors Code:		Red	Rejected.	Yellow	2 nd Class	Orange	3 rd Class	Blue	Need Repair	Green	Need Hard Banding

Inspector Name:	SHERIF MOHAMED	Review By				
Qualification:	ASNT Level II (MT, UT)	Senior Inspector:	MOHAMED FAHAD	Supervisor:	MOHAMED WAQAS	Customer Name:
Signature:						Customer Signature:
Original - Client Files		Copy - Area Office		QC/FN/DJ-PB/029 Rev.00 dated 07.Nov2021		

