



9-5/8" VAM TOP CASING INSPECTION SUMMARY

Customer	DAQING DRILLING	Date Of Service	14.FEB.2024
Location	DQ -38 (RU-600)	References	API SPEC 5CT / API RP 5A5 / VAM SPECIFICATION

DESCRIPTION	
Casing 9 5/8 " OD, Weight 47.00 lb/ft, Grede, L-80, Range III with VAMTOP Connection Inspected	


Procedure of Inspecting The Pin and Box End Connection. Which details such as below	
1-Check that the coupling is made-up tightly and there is no gap at the shoulder.	
2-Check that the coupling has not been over torqued and has yielded.	
3-Check the correct weight of coupling is fitted and that there is no step at the shoulder.	
4-Check that there is no plastic pressure test seals left inside the connection. (Teflon seals are not recommended by VAM)	
5-Check that Dents, dings or mashes caused by impact.	
6-Check that Gallling caused by a poor make-up.	
7-Check that Rust, corrosion or pitting caused by the enviroment.	

PIN & BOX VAM TOP CONNECTION INSPECTED AREA	
Box Thread: Counter bore, Torque shoulder, Seal area, Cylindrical part, Perfect thread length, face.	
Pin Thread: Imperfect thread length, Perfect thread length, Cylindrical part, Seal area, Radius between seal and shoulder, Torque shoulder, Internal weight counterbore.	

VAM TOP TECHNICAL DATA												
SIZE (OD) in	Nominal Weight lb/ft	Wall Thickness in	API Drift Diameter in	Coupling OD(reg)	Coupling ID(reg) in	Make-up Loss in	Coupling Length in	Pipe Body Section sq.in	Coupling CCS sq.in	Coupling Face Area sq.in		
9-5/8"	47.0	0.472	8.525	10.396	8.858	5.589	13.190	13.572	13.838	7.870		
Regular Yield Strength (1000 lb)												
55 Ksi		80 Ksi		90 Ksi		95 Ksi		110 Ksi		125 Ksi	140 Ksi	150 Ksi
746		1086		1222		1289		1493		1967	1900	2036
NOTE:		Running Vam Top- Dop quantities required Dope volume 41 cm ³ or 2.5 in ³ .										

FINAL RESULTS

- * 163 No's of Casing Joints 9 5/8" OD, Weight 47.00 lb/ft, Grede, L-80, Range 3 with VAMTOP Connection Inspected.
- * 160 No's of Casing Joints Were Found "Acceptable" At The Time of Inspection .
- * 03 No's of Casing Joints Were Found "Not Acceptable" From Side Pin &Box At The Time of Inspection .



PERSON DETAILS		REVIEW BY	
INSPECTOR NAME:	SHERIF MOHAM	SENIOR INSPECTOR:	NAVEED HUSSAIN
QUALIFICATION:	ASNT LEVEL II MT, PT, U	INSPECTION SUPERVISOR:	M.WAQAS
SIGNATURE & STAMP		CLIENT:	



9 5/8" VAM TOP NEW CASING VISUAL INSPECTION CERTIFICATE

Client Name:		DAQING DRILLING		Date:	14.FEB.2024	
Location/Rig:		DQ-38(RU-600)		Report No.:	QC-24-FEB-0059-DQ38-001	
SPECIFICATION:		API Specification 5A5&5ct,10th Edition /VAM SPECIFICATION			Make-up Loss	5.589
Wall Thickness	0.472	9 5/8"VAM TOP 47.00PPF VAM TOP L-80			ID: 8.681"	OD: 9 5/8" Drift: 8.525"
Joint designation		Total Length	Visual Thread Inspection			END AREAS
SERIAL:NO	Actual # on JT.	(m)	Thread Profile Gauge	PIN	BOX	
1	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	
2	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
3	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
4	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
5	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
6	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
7	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
8	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
9	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
10	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
11	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
12	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
13	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
14	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
15	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
16	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
17	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
18	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
19	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	S.D	OK	REJECTED
20	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
21	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
22	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
23	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
24	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
25	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
26	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
27	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
28	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
29	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
30	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
Inspector Name:	SHERIF MOHAMMAD	Review By				
Qualification:	ASNT Level II (MT, PT, UT)	Senior Inspector:	NAVEED HUSSAIN	Supervisor:	M.WAQAS	Customer Name:
Signature:						Customer Signature:

Original - Client Files

Copy - Area Office

QC/FN/DJ-PB/029

Rev.00 dated 07.Nov2021





9 5/8" VAM TOP NEW CASING VISUAL INSPECTION CERTIFICATE

Client Name:		DAQING DRILLING		Date:	14.FEB.2024	
Location/Rig:		DQ-38(RU-600)		Report No.:	QC-24-FEB-0059-DQ38-002	
SPECIFICATION:		API Specification 5A5&5ct,10th Edition /VAM SPECIFICATION			Make-up Loss	5.589
Wall Thickness	0.472	9 5/8"VAM TOP 47.00PPF VAM TOP L-80			ID: 8.681"	OD: 9 5/8" Drift: 8.525"
Joint designation		Total Length	Visual Thread Inspection			END AREAS
SERIAL:NO	Actual # on JT.	(m)	Thread Profile Gauge	PIN	BOX	
31	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	
32	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
33	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
34	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
35	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
36	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
37	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
38	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
39	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
40	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
41	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
42	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
43	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
44	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
45	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
46	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
47	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
48	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
49	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
50	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
51	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
52	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
53	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
54	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
55	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
56	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
57	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
58	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
59	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
60	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
Inspector Name:	SHERIF MOHAMED	Review By				
Qualification:	ASNT Level II (MT, PT, UT)	Senior Inspector:	NAVEED HUSSAIN	Supervisor:	M.WAQAS	Customer Name:
Signature:						Customer Signature:

Original - Client Files

Copy - Area Office

QC/FN/DJ-PB/029

Rev.00 dated 07.Nov2021





9 5/8" VAM TOP NEW CASING VISUAL INSPECTION CERTIFICATE

Client Name:		DAQING DRILLING		Date:	14.FEB.2024	
Location/Rig:		DQ-38(RU-600)		Report No.:	QC-24-FEB-0059-DQ38-003	
SPECIFICATION:		API Specification 5A5&5ct,10th Edition /VAM SPECIFICATION			Make-up Loss	5.589
Wall Thickness	0.472	9 5/8"VAM TOP 47.00PPF VAM TOP L-80			ID: 8.681"	OD: 9 5/8" Drift: 8.525"
Joint designation		Total Length	Visual Thread Inspection			END AREAS
SERIAL:NO	Actual # on JT.	(m)	Thread Profile Gauge	PIN	BOX	
61	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	
62	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
63	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
64	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
65	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
66	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
67	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
68	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	S.D	OK	REJECTED
69	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
70	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
71	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
72	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
73	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
74	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
75	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
76	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
77	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
78	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
79	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
80	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
81	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
82	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
83	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
84	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
85	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
86	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
87	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
88	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
89	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
90	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
Inspector Name:	SHERIF MOHAMED	Review By				
Qualification:	ASNT Level II (MT, PT, UT)	Senior Inspector:	NAVEED HUSSAIN	Supervisor:	M.WAQAS	Customer Name:
Signature:						Customer Signature:
Original - Client Files		Copy - Area Office		QC/FN/DJ-PB/029		Rev.00 dated 07.Nov2021





9 5/8" VAM TOP NEW CASING VISUAL INSPECTION CERTIFICATE

Client Name:		DAQING DRILLING		Date:	14.FEB.2024	
Location/Rig:		DQ-38(RU-600)		Report No.:	QC-24-FEB-0059-DQ38-004	
SPECIFICATION:		API Specification 5A5&5ct,10th Edition /VAM SPECIFICATION			Make-up Loss	5.589
Wall Thickness	0.472	9 5/8"VAM TOP 47.00PPF VAM TOP L-80			ID: 8.681"	OD: 9 5/8" Drift: 8.525"
Joint designation		Total Length	Visual Thread Inspection			END AREAS
SERIAL:NO	Actual # on JT.	(m)	Thread Profile Gauge	PIN	BOX	
91	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	
92	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
93	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
94	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
95	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
96	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
97	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
98	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
99	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
100	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
101	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
102	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
103	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
104	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
105	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
106	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
107	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
108	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
109	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
110	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
111	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
112	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
113	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
114	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
115	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
116	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
117	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
118	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
119	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
120	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
Inspector Name:	SHERIF MOHAMAD	Review By				
Qualification:	ASNT Level II (MT, PT, UT)	Senior Inspector:	NAVEED HUSSAIN	Supervisor:	M.WAQAS	Customer Name:
Signature:						Customer Signature:

Original - Client Files

Copy - Area Office

QC/FN/DJ-PB/029

Rev.00 dated 07.Nov2021





9 5/8" VAM TOP NEW CASING VISUAL INSPECTION CERTIFICATE

Client Name:		DAQING DRILLING		Date:	14.FEB.2024	
Location/Rig:		DQ-38(RU-600)		Report No.:	QC-24-FEB-0059-DQ38-005	
SPECIFICATION:		API Specification 5A5&5ct,10th Edition /VAM SPECIFICATION			Make-up Loss	5.589
Wall Thickness	0.472	9 5/8"VAM TOP 47.00PPF VAM TOP L-80			ID: 8.681"	OD: 9 5/8" Drift: 8.525"
Joint designation		Total Length	Visual Thread Inspection			END AREAS
SERIAL:NO	Actual # on JT.	(m)	Thread Profile Gauge	PIN	BOX	
121	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	
122	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
123	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
124	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
125	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
126	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
127	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
128	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
129	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
130	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
131	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
132	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
133	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
134	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
135	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
136	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
137	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
138	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
139	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
140	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
141	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
142	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
143	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
144	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
145	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
146	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
147	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
148	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
149	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
150	9 5/8' VAM TOP47.00# PPF VAM TOP CASING JOINT	-	OK	OK	OK	READY TO USE
Inspector Name:	SHERIF MOHAMED	Review By				
Qualification:	ASNT Level II (MT, PT, UT)	Senior Inspector:	NAVEED HUSSAIN	Supervisor:	M.WAQAS	Customer Name:
Signature:						Customer Signature:
Original - Client Files		Copy - Area Office		QC/FN/DJ-PB/029 Rev.00 dated 07.Nov2021		



