



### CERTIFICATE OF INSPECTION FOR 8" DRILL COLLAR

<b>Client Name:</b>	<b>DAQING DRILLING</b>	<b>Report No.:</b>	DQ-37-QC-24-04-RS-001
<b>Acceptance Creater:</b>	DS-1 Fifth Edition, Volume 3 CAT 3-5	<b>Date of Inspection:</b>	16.APR.2024
<b>Work Location:</b>	RU-610	<b>Rig No.:</b>	DQ-37
<b>Test Equipment &amp; Consumeable Details</b>			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN,2025	<b>TECHNICAL DETAILS</b>	Wet Visible Continuous
BLACK INK 7HF	Batch#: 220605 Manufacture: Magnaflux Exp Date: JULY.2025	COIL(1200 AMP-TURNS/IN	SC 22713 Cal.15.FEB.2024 Cal Due14.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March.2025	A.C HAND YOKE	201504053 Cal.15.FEB.2024 Cal Due14.AUG.2024
INTENSITY METER	SR#1608000134 CAL.Date Cal. 15.FEB.2024 Cal Due 14.AUG.2024	UV BLACK LIGHT	SR#1900084 Cal.15.FEB.2024 Cal Due14.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 Cal. 13.FEB.2024 Cal Due 12.AUG.2024	THREAD PROFILE GAGE	SR#21336 Cal. 13.FEB.2024 Cal Due 12.AUG.2024 SR#21335 Cal. 15.FEB.2024 Cal Due 14.AUG.2024
Magnetic Partical Concentration 7 HF	1.2 TO 2.4 ML/100 ML	WMPT Light Intensity	3400 Lux
Magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	UV LIGHT INTENSITY:	2950 µw/cm <sup>2</sup>
Magnetism Direction (Longitudinal)			
<b>METHODOLOGY:</b>	<ul style="list-style-type: none"> <li>• Through Visual inspection</li> <li>• MPI inspection with Ultraviolet light</li> <li>• Dimensional 3</li> </ul>		
<b>Connection:</b>	<b>6 5/8 REG</b>	<b>Size:</b>	<b>8"</b>

Serial No.	Visual Inspection			MPI			Dimensional 3 Inspection																
	Pin	Box	Body	Pin	Box	Body	Pin					Box					Body						
							OD (in)	ID (in)	SRG □ (in)	SRG W □ (in)	Pin □ (in)	Bevel □ (in)	OD (in)	CBD □ (in)	CBW □ (in)	BB □ (in)	BBL □ (in)	Bevel □ (in)	Pin Tong □ (in)	Box Tong □ (in)	EGR □ (in)	SGR □ (in)	Overall □ (in)
0500008 6	SRG.P&G.T	NO B.B&G.T	Acc.	Acc.	Acc.	Acc.	8 1/16"	2 7/8"	5 3/8"	3/4"	4 15/16"	7 1/2"	8 1/16"	6 1/16"	5/8"	-	-	7 1/2"	18 3/8"	42 7/8"	-	7/32"	-

**Conclusion:** 01 DRILL COLLARS above were found "UnAcceptable" From Pin Connection SRG Pitted&Galled Thread Box Connection Galled Thread& No BoreBack Rejected..Need BoreBack.

**Abbreviations :**

<b>OD</b> Outside Diameter	<b>ID</b> Inside Diameter	<b>SRG</b> Stress Relief Groove	<b>CB</b> Counter Bore	<b>BB</b> Bore Back	<b>FB</b> Float Bore	
□ Diameter	□ Length	□ Width	□ Depth	<b>NP.</b> Not Present	<b>NA.</b> Not Applicable	
<b>EGR</b> Elevator Groove Recess	<b>SGR</b> Slip Groove Recess	<b>CR</b> Crack	<b>B</b> Bent	<b>PC</b> Premium Class	<b>RF</b> Reface	
<b>GT</b> Galled Thread	<b>PT</b> Pitting Thread	<b>SP</b> Seal Pitting	<b>TD</b> Thread Damage	<b>SD</b> Seal Damage	<b>M</b> Mashed	
<b>1</b> 100 % Coating	<b>2</b> 99-71 % Coating	<b>3</b> 70-40 % Coating	<b>4</b> Up to 40 %	<b>5</b> Nil	<b>WT</b> Wall Thickness	
<b>Colors Code:</b>		<b>White</b> No Defects	<b>Red</b> Crack or Extreme Damage.	<b>Blue</b> Damage	<b>Green</b> Seal Damage	<b>Yellow</b> ACFM

<b>Inspector Name:</b>	RAJESH CHAL	<b>Review By</b>			
<b>Qualificatio</b>		<b>Senior Inspector:</b>	M.FAHAD	<b>Supervisor:</b>	WAQAS
<b>Signature:</b>				<b>Customer Name:</b>	
				<b>Customer Signature:</b>	
Original - Client Files Copy - Area Office QC/FN/AF,REP/026 Rev.00 Dated 01 AUG 2021					

