



### CERTIFICATE OF INSPECTION FOR 9" DRILL COLLAR

<b>Client Name:</b>	<b>DAQING DRILLING</b>	<b>Report No.:</b>	DQ-11-QC-24-03-RS-007
<b>Acceptance Creater:</b>	DS-1 Fifth Edition, Volume 3 CAT 3-5	<b>Date of Inspection:</b>	22.MAR.2024
<b>Work Location:</b>	(R-104A)	<b>Rig No.:</b>	DQ-11
<b>Test Equipment &amp; Consumeable Details</b>			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN.2025	<b>TECHNICAL DETAILS</b>	Wet Visible Continuous
BLACK INK 7HF	Batch#: 220605 Manufacture: Magnaflux Exp Date: JULY.2025	COIL(1200 AMP-TURNS/IN	SC 22713 Cal.15.FEB.2024 Cal Due14.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March.2025	A.C HAND YOKE	201504053 Cal.15.FEB.2024 Cal Due14.AUG.2024
INTENSITY METER	SR#160800134 CAL.Date Cal. 15.FEB.2024 Cal Due 14.AUG.2024	UV BLACK LIGHT	SR#1900084 Cal.15.FEB.2024 Cal Due14.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 Cal. 13.FEB.2024 Cal Due 12.AUG.2024	THREAD PROFILE GAGE	SR#21336 Cal. 13.FEB.2024 Cal Due 12.AUG.2024 SR#21335 Cal. 15.FEB.2024 Cal Due 14.AUG.2024
Magnetic Partical Concentration 7 HF	1.2 TO 2.4 ML/100 ML	WMPT Light Intensity	3120 Lux
Magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	UV LIGHT INTENSITY:	2950 µw/cm <sup>2</sup>
Magnetism Direction (Longitudinal)			
<b>METHODOLOGY:</b>	<ul style="list-style-type: none"> <li>• Through Visual inspection</li> <li>• MPI inspection with Ultraviolet light</li> <li>• Dimensional 3</li> </ul>		
<b>Connection:</b>	<b>7 5/8 REG</b>	<b>Size:</b>	<b>9"</b>

Serial No.	Visual Inspection			MPI			Dimensional 3 Inspection																	
	Pin	Box	Body	Pin	Box	Body	Pin					Box					Body							
							OD (in)	ID (in)	SRG □ (in)	SRG W □ (in)	Pin □ (in)	Bevel □ (in)	OD (in)	CBD □ (in)	CBW □ (in)	BB □ (in)	BBL □ (in)	Bevel □ (in)	Pin Tong □ (in)	Box Tong □ (in)	EGR □ (in)	SGR □ (in)	Overall □ (in)	
28124	Acc.	Acc.	Acc.	Acc.	Acc.	Acc.	9"	2 7/8"	6 11/32"	1"	5 1/4"	8 3/8"	9"	7 1/16"	5/8"	5 55/64"	9"	8 3/8"	21 3/8"	20 3/4"	-	9/32"	-	

**Conclusion:** ■ 0 1 DRILL COLLARS above were found "Acceptable". At the time of Inspection (Ready for Use).

**Abbreviations :**

<b>OD</b> Outside Diameter	<b>ID</b> Inside Diameter	<b>SRG</b> Stress Relief Groove	<b>CB</b> Counter Bore	<b>BB</b> Bore Back	<b>FB</b> Float Bore
□ Diameter	□ Length	□ Width	□ Depth	<b>NP.</b> Not Present	<b>NA.</b> Not Applicable
<b>EGR</b> Elevator Groove Recess	<b>SGR</b> Slip Groove Recess	<b>CR</b> Crack	<b>B</b> Bent	<b>PC</b> Premium Class	<b>RF</b> Reface
<b>GT</b> Galled Thread	<b>PT</b> Pitting Thread	<b>SP</b> Seal Pitting	<b>TD</b> Thread	<b>SD</b> Seal Damage	<b>M</b> Mashed
<b>1</b> 100 % Coating	<b>2</b> 99-71 % Coating	<b>3</b> 70-40 % Coating	<b>4</b> Up to 40 %	<b>5</b> Nil	<b>WT</b> Wall Thickness
<b>Colors Code:</b>					
<span style="background-color: white; border: 1px solid black;">White</span> No Defects	<span style="background-color: red; border: 1px solid black;">Red</span> Crack or Extreme Damage.	<span style="background-color: blue; border: 1px solid black;">Blue</span> Damage	<span style="background-color: green; border: 1px solid black;">Green</span> Seal Damage	<span style="background-color: yellow; border: 1px solid black;">Yellow</span> ACFM	

<b>Inspector Name:</b>	RAC MUTHAIL	<b>Review By</b>			
<b>Qualification:</b>	Senior Inspector	<b>Supervisor:</b>	WAQAS AWAN	<b>Customer Name:</b>	
<b>Signature:</b>				<b>Customer Signature:</b>	
Original - Client Files      Copy - Area Office      QC/FN/AF,REP/026 Rev.00 Dated 01 AUG 2021					

