

AI TAKAMUL COMPANY FOR ENGINEERING TESTS AND PROFESSIONAL SAFETY LIMITED

Basra, North Rumaila, Quality Control Yard - Iraq

Tel: +9647810009138 / +9647834964657

Email: OP@qualitycontrol-iraq.com / hany.akafi@qualitycontrol-iraq.com



INSPECTION CERTIFICATE OF BOTTEL NECK X-OVER#D11-6

Client Name:	DAQING DRILLING	Report No.:	DQ-11-QC-24-03-RS-014
Acceptance Createra.	DS-1 Fifth Edition, Volume 3 CAT 3-5	Date of Inspection:	22.MAR.2024
Work Location:	(R-104A)	Rig No.:	DQ-11
Test Equipment & Consumeable Details			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN,2025	TECHNICAL DETAILS	Wet Visible Continuous
BLACK INK 7HF	Batch#:220605 Manufacture: Magnaflux Exp Date: JULY.2025	COIL(1200 AMP-TURNS/IN	SC 22713 Cal.15.FEB.2024 Cal Due 14.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March.2025	A.C HAND YOKE	201504053 Cal.15.FEB.2024 Cal Due 14.AUG.2024
INTENSITY METER	SR#1608000134 CAL.Date Cal. 15.FEB.2024 Cal Due 14.AUG.2024	UV BLACK LIGHT	SR#1900084 Cal.15.FEB.2024 Cal Due 14.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 Cal. 13.FEB.2024 Cal Due 12.AUG.2024	THREAD PROFILE GAGE	SR#21336 Cal. 13.FEB.2024 Cal Due 12.AUG.2024 SR#21335 Cal. 15.FEB.2024 Cal Due 14.AUG.2024
Magnetic Partical Concentration 7 HF	1.2 TO 2.4 ML/100 ML	WMPT Light Intensity	3120 Lux
Magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	UV LIGHT INTENSITY:	2950 μw/cm ²
Magnetism Direction (Longitudinal)			
METHODOLOGY:	<ul style="list-style-type: none"> • Through Visual inspection • MPI inspection with Ultraviolet light • Dimensional 3 		

Serial No.	Description	Connection		Result Inspection			Dimensional3- Inspection														
		Pin	Box	Pin	Box	Body	Pin					Box					Body				
							OD(In)	ID(In)	SRG □(In)	SRG W □(In)	Pin □(In)	Bevel □(In)	OD(In)	CB □(In)	CB □(In)	BBB □(In)	BBL □(In)	Bevel □(In)	Tongspac e (In)□	Box Lth (In)□	Overall □(In)
D11-6	BOTTEL NECK X-OVER	6 5/8"Reg	NC50	Acc	S.D&T. PNO B.B	Acc	8"	2 7/8"	5 3/8"	13/16"	5"	7 1/2"	6 3/4"	5 5/16"	5/8"	-	-	6 1/4"	8 1/2"	17"	27"
Conclusion :		<p><i>*01 BOTTEL NECK X-OVER above was found "UnAcceptable". From Box Connection Seal Damage&Thread Pitted Rejected.NOTE:NO BOREBACK. Pin Stress Relief Groove: Unless waived by the customer, all APIconnection NC38 and larger that make up to BHA components shall be equipped with pin stress relief grooves or they shall be rejected they diameter and width of the API pin strss relief grooves shall be measured and shall meet the erquirements of table 3.25.4</i></p>																			

OD Outside Diameter	ID Inside Diameter	SRG Stress Relief Groove	CB Counter Bore	BB Bore Back	FB Float Bore	
□ Diameter	□ Length	□ Width	□ Depth	NP. Not Present	NA. Not Applicable	
EGR Elevator Groove Recess	SGR Slip Groove Recess	CR Crack	B Bent	PC Premium Class	RF Reface	
GT Galled Thread	TP Thread Pitting	SP Seal Pitting	TD Thread Damage	SD Seal Damage	M Mashed	
1 100 % Coating	2 99-71 % Coating	3 70-40 % Coating	4 Up to 40 %	5 Nil	WT Wall Thickness	
Colors Code:		White No Defects	Red Crack or Extreme	Blue Damage	Green Seal Damage	Yellow ACFM

Inspector Name:	RAQ SOHAIL	Review By			
Qualifica:	ASNT Level I	Senior Inspector:	M.FAHAD	Supervisor:	WAQAS AWAN
Signature:					Customer Name:
					Customer Signature:
Original - Client Files		Copy - Area Office		QC/FN/DJ-PB/029 Rev.00 dated 07.Nov2021	

