

AI TAKAMUL COMPANY FOR ENGINEERING TESTS AND PROFESSIONAL SAFETY LIMITED

Basra, North Rumaila, Quality Control Yard - Iraq

Tel: +9647810009138 / +9647834964657

Email: OP@qualitycontrol-iraq.com / hany.akafi@qualitycontrol-iraq.com



INSPECTION CERTIFICATE OF 7" MAGNETIC SUB

Client Name:	DAQING DRILLING	Report No.:	DQ-11-QC-24-03-RS-019
Acceptance Createra.	DS-1 Fifth Edition, Volume 4	Date of Inspection:	22.MAR.2024
Work Location:	(R-104A)	Rig No.:	DQ-11
Test Equipment & Consumeable Details			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN,2025	TECHNICAL DETAILS	Wet Visible Continuous
BLACK INK 7HF	Batch#:220605 Manufacture: Magnaflux Exp Date: JULY.2025	COIL(1200 AMP-TURNS/IN	SC 22713 Cal.15.FEB.2024 Cal Due14.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March.2025	A.C HAND YOKE	201504053 Cal.15.FEB.2024 Cal Due14.AUG.2024
INTENSITY METER	SR#1608000134 CAL.Date Cal. 15.FEB.2024 Cal Due 14.AUG.2024	UV BLACK LIGHT	SR#1900084 Cal.15.FEB.2024 Cal Due14.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 Cal. 13.FEB.2024 Cal Due 12.AUG.2024	THREAD PROFILE GAGE	SR#21336 Cal. 13.FEB.2024 Cal Due 12.AUG.2024 SR#21335 Cal. 15.FEB.2024 Cal Due 14.AUG.2024
Magnetic Partical Concentration 7 HF	1.2 TO 2.4 ML/100 ML	WMPT Light Intensity	3120 Lux
Magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	UV LIGHT INTENSITY:	2950 μw/cm ²
Magnetism Direction (Longitudinal)			
METHODOLOGY:	<ul style="list-style-type: none"> • Through Visual inspection • Dimensional • MPI inspection with Ultraviolet light 		

Serial No.	Description	Connection		Result Inspection			Dimensional- Inspection														
		Pin	Box	Pin	Box	Body	Pin						Box					Body			
							OD(In)	ID(In)	SRG □(In)	SRG W □(In)	Pin □(In)	Bevel □(In)	OD(In)	CB □(In)	CB □(In)	BBD □(In)	BBL □(In)	Bevel □(In)	Tongspac e (In) □	Box Lth (In) □	Overall □(In)
3825230 162	MAGNETIC	NC38	NC38	Acc.	Acc.	Acc.	5"	2"	3 1/2"	1"	4"	4 5/8"	5"	4 1/16"	5/8	-	-	4 5/8"	-	-	79"
Conclusion :		*01 MAGNETIC SUB above was found "Acceptable". At the time of Inspection (Ready for Use).																			

OD □	Outside Diameter	ID □	Inside Diameter	SRG □	Stress Relief Groove	CB □	Counter Bore	BB	Bore Back	FB	Float Bore
	Diameter		Length		Width		Depth	NP.	Not Present	NA.	Not Applicable
EGR	Elevator Groove Recess	SGR	Slip Groove Recess	CR	Crack	B	Bent	PC	Premium Class	RF	Reface
GT	Galled Thread	TP	Thread Pitting	SP	Seal Pitting	TD	Thread	SD	Seal Damage	M	Mashed
1	100 % Coating	2	99-71 % Coating	3	70-40 % Coating	4	Up to 40 %	5	Nil	WT	Wall Thickness
Colors Code:		White	No Defects	Red	Crack or Extreme	Blue	Damage	Green	Seal Damage	Yellow	ACFM

Inspector Name:	WAQAS AWAN	Review By			
Qualification:	ASNT Level I	Senior Inspector:	M.FAHAD	Supervisor:	WAQAS AWAN
Signature:				Customer Name:	
				Customer Signature:	
Original - Client Files		Copy - Area Office		QC/FN/DJ-PB/029 Rev.00 dated 07.Nov2021	

