



CERTIFICATE OF INSPECTION FOR 6 3/4" DRILL COLLAR

Client Name:	DAQING DRILLING	Report No.:	DQ-22-QC-24-05-RS-007
Acceptance Creater:	DS-1 Fifth Edition, Volume 3 CAT 3-5	Date of Inspection:	29.MAY.2024
Work Location:	RU-618	Rig No.:	DQ-22
Test Equipment & Consumeable Details			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN.2025	TECHNICAL DETAILS	Wet Visible Continuous
BLACK INK 7HF	Batch#: 220605 Manufacture: Magnaflux Exp Date: JULY.2025	COIL(1200 AMP-TURNS/IN	SC 22713 Cal.15.FEB.2024 Cal Due14.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March.2025	A.C HAND YOKE	201504053 Cal.15.FEB.2024 Cal Due14.AUG.2024
INTENSITY METER	SR#1608000134 CAL.Date Cal. 15.FEB.2024 Cal Due 14.AUG.2024	UV BLACK LIGHT	SR#1900084 Cal.15.FEB.2024 Cal Due14.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 Cal. 13.FEB.2024 Cal Due 12.AUG.2024	THREAD PROFILE GAGE	SR#21336 Cal. 13.FEB.2024 Cal Due 12.AUG.2024 SR#21335 Cal. 15.FEB.2024 Cal Due 14.AUG.2024
Magnetic Partical Concentration 7 HF	1.2 TO 2.4 ML/100 ML	WMPT Light Intensity	3500 Lux
Magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	UV LIGHT INTENSITY:	3050 μw/cm ²
Magnetism Direction (Longitudinal)			
METHODOLOGY:	- Through Visual inspection - MPI inspection with Ultraviolet light - Dimensional 3		
Connection:	NC50	Size:	6 3/4"

Serial No.	Visual Inspection			MPI			Dimensional 3 Inspection																			
							Pin						Box						Body							
	Pin	Box	Body	Pin	Box	Body	OD (in)	ID (in)	SRG ² (in)	SRG W ² (in)	Pin ² (in)	Bevel ² (in)	OD (in)	CBD ² (in)	CBW ² (in)	BB ² (in)	BBL ² (in)	Bevel ² (in)	Pin Tong ² (in)	Box Tong ² (in)	EGR ² (in)	SGR ² (in)	Overall ² (In)			
77775	Acc.	S.D	Acc.	Acc.	Acc.	Acc.	6 ¾"	2 7/8"	⁴ 23/32"	¾"	4 ½"	6 5/16"	6 ¾"	⁵ 5/16"	5/8"	4 5/8"	8 1/8"	6 5/16"	18 ¾"	21 ¼"	-	7/32"	-			
Conclusion:			■01 DRILL COLLARS above were found "UnAcceptable" From Box Connection Seal Damage Rejected.																							

Conclusion: 01 DRILL COLLARS above were found "UnAcceptable" From Box Connection Seal Damage Rejected.

Abbreviations :

OD	Outside Diameter	ID	Inside Diameter	SRG	Stress Relief Groove	CB	Counter Bore	BB	Bore Back	FB	Float Bore
□	Diameter	□	Length	□	Width	□	Depth	NP.	Not Present	NA.	Not Applicable
EGR	Elevator Groove Recess	SGR	Slip Groove Recess	CR	Crack	B	Bent	PC	Premium Class	RF	Reface
GT	Galled Thread	PT	Pitting Thread	SP	Seal Pitting	TD	Thread Damage	SD	Seal Damage	M	Mashed
1	100 % Coating	2	99-71 % Coating	3	70-40 % Coating	4	Up to 40 %	5	Nil	WT	Wall Thickness
Colors Code:		White No Defects		Red	Crack or Extreme Damage.	Blue	Damage	Green	Seal Damage	Yellow	ACFM

Inspector Name:	RAD RUMAIL	Review By	
Qualification:	ASNT Level 2	Senior Inspector:	M.FAHAD
Signature:		Supervisor:	WAQAS AWAN
		Customer Name:	
		Customer Signature:	

Original - Client Files

Copy - Area Office

QC/FN/AF,REP/026 Rev.00 Dated 01 AUG 2021

