



Client Name:	ZHONGMAN PETROLEUM AND NATURAL GAS GROUP CROP,LTD	Report No.:	ZPEC-25-QC-24-05-RS-014
Acceptance Createra.	DS-1 Fifth Edition, Volume 3 CAT 3-5	Date of Inspection:	23.MAY.2024
Work Location:	AW-66	Rig No.:	ZPEC-25
Test Equipment & Consumeable Details			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN,2025	TECHNICAL DETAILS	Wet Visible Continuous
BLACK INK 7HF	Batch#:220605 Manufacture: Magnaflux Exp Date: JULY.2025	COIL(1200 AMP-TURNS/IN	SC 22713 Cal.15.FEB.2024 Cal Due14.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March.2025	A.C HAND YOKE	201504053 Cal.15.FEB.2024 Cal Due14.AUG.2024
INTENSITY METER	SR#1608000134 CAL.Date Cal. 15.FEB.2024 Cal Due 14.AUG.2024	UV BLACK LIGHT	SR#1900084 Cal.15.FEB.2024 Cal Due14.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 Cal. 13.FEB.2024 Cal Due 12.AUG.2024	THREAD PROFILE GAGE	SR#21336 Cal. 13.FEB.2024 Cal Due 12.AUG.2024 SR#21335 Cal. 15.FEB.2024 Cal Due 14.AUG.2024
Magnetic Partical Concentration 7 HF	1.2 TO 2.4 ML/100 ML	WMPT Light Intensity	3520 Lux
Magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	UV LIGHT INTENSITY:	2950 μw/cm²
Magnetism Direction (Longitudinal)			
METHODOLOGY:	Through Visual inspection • Dimensional	•MPI inspection with Ultraviolet light Heat Checking	Thread Profile Gauging.
Connection:	NC50	Size:	5"

Serial No.	Visual Inspection				Black Light		Dimensional 3 Inspection															
							Pin						Box						Body			
	Pin	Box	Body	HB	Pin	Box	OD (in)	ID (in)	SRG ϕ (in)	SRG λ (in)	Bevel ϕ (in)	pin λ (in)	OD (in)	CB ϕ (in)	CB δ (in)	BB ϕ (in)	BB δ (in)	Bevel ϕ (in)	Seal ϖ	Pin Tong λ (in)	Box Tong λ (in)	Center Pnd ϕ (in)
JZ1218-490	SRG: P	Acc	Acc	✓	Acc	Acc	6 9/16"	3 1/16"	4 23/32"	¾"	6 1/16"	4 ½"	6 9/16"	5 5/16"	5/8"	4 5/8"	8 ½"	6 1/8"	14/32"	19 7/8"	26 ¾"	5 ½"
JZ1218-481	SRG: P	Acc	Acc	✓	Acc	Acc	6 9/16"	3 1/16"	4 23/32"	¾"	6 1/16"	4 ½"	6 9/16"	5 5/16"	5/8"	4 5/8"	8"	6 1/8"	14/32"	15"	20 7/8"	5 ½"
JZ1218-502	SRG: P	Acc	Acc	✓	Acc	Acc	6 9/16"	3 1/16"	4 23/32"	1"	6 1/16"	4 ½"	6 9/16"	5 5/16"	5/8"	4 5/8"	8 ½"	6 1/8"	14/32"	16 ¼"	21 ½"	5 ½"
Conclusion:		The Above Mentioned 5" Heavy Weight Drill Pipe was Found UnAcceptable from Pin Connection SRG Pitted Rejected.																				

OD	Outside Diameter	ID	Inside Diameter	SRG	Stress Relief Groove	CB	Counter Bore	BB	Bore Back	FB	Float Bore
Φ	Diameter	λ	Length	ω	Width	δ	Depth	NP	Not Present	NA	Not Applicable
EGR	Elevator Groove Recess	SGR	Slip Groove Recess	CR	Crack	B	Bent	PC	Premium Class	RF	Reface
GT	Galled Thread	TP	Thread Pitting	SP	Seal Pitting	TD	Thread Damage	SD	Seal Damage	M	Mashed
1	100 % Coating	2	99-71 % Coating	3	70-40 % Coating	4	Up to 40 %	5	Nil	WT	Wall Thickness
Colors Code:		White	No Defects	Red	Crack or Extreme	Blue	Damage	Green	Seal Damage	Yellow	ACFM

Inspector Name:	EAC SCHAL		Review By				
Qualification	APPL. CIVIL	Senior Inspector:	M. FAHAD	Supervisor:	MOHAMED WAQAS	Customer Name:	
Signature:						Customer Signature:	
Original - Client Files		Copy - Area Office		QC/FN/DJ-PB/029 Rev.00 dated 07.Nov2021			

