


AI TAKAMUL COMPANY FOR ENGINEERING TESTS AND PROFESSIONAL SAFETY LIMITED

Basra, North Rumaila, Quality Control Yard - Iraq

Tel: +9647810009138 / +9647834964657



INSPECTION CERTIFICATE FOR 17 1/2" ROLLER REAMER#DEP-17-0663

Client Name:	AL-ESNAAD OIL TOOL FOR OIL SERVICES.LLC	Report No.:	QC-24-05-AL-ESNAAD-027
Acceptance criteria.	DS-1 Fifth Edition, Volume 4	Date of Inspection:	13.MAY.2024
Work Location:	AL-ESNAAD OIL TOOL YARD		
TEST EQUIPMENT & CONSUMABLE DETAILS			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN.2025	TECHNICAL DETAILS	Wet Visible Continuous
BLACK INK 7HF	Batch#: 220605 Manufacture: Magnaflux Exp Date: JULY.2025	COIL(1200 AMP-TURNS/IN	SC 22713 Cal.15.FEB.2024 Cal Due14.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March.2025	A.C HAND YOKE	201504053 Cal.15.FEB.2024 Cal Due14.AUG.2024
INTENSITY METER	SR#1608000134 CAL.Date Cal. 15.FEB.2024 Cal Due 14.AUG.2024	UV BLACK LIGHT	SR#1900084 Cal.15.FEB.2024 Cal Due14.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 Cal. 13.FEB.2024 Cal Due 12.AUG.2024	THREAD PROFILE GAGE	SR#21336 Cal. 13.FEB.2024 Cal Due 12.AUG.2024
Magnetic Partical Concentration 7HF	1.2 TO 2.4 ML/100 ML		SR#21335 Cal. 15.FEB.2024 Cal Due 14.AUG.2024
magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	WMPT Light Intensity	3450 Lux
RING GAUGE	DES 17 1/2" RING GAUGE SR # ITS-004) CAL.Date.04.SEP.2023 CAL Due Date. 03.SEP.2024	UV LIGHT INTENSITY:	3000 μw/cm ²
MAGNITISUM DIRECTION (LONGITUDENAL)			
METHODOLOGY:	- Through Visual inspection - Dimensional 3 - MPI inspection with Ultraviolet light		
ROLLER REAMER 17 1/2"			

Serial No.	Connection		Condition			Dimensional 3 Inspection																
	Pin	Box	Pin	Box	Body	Pin						Box						Body				
						OD	ID (F)	PIN λ(In)	SRG ϕ	SRG (In)	BEVEL ϕ	OD	CB ϕ	CB λ(In)	BBϕ	BBλ(In)	BEVEL ϕ	Fishing Neck (A)	Blade Length (B)	Down Length (C)	Overall Length(D) (in)	Blade Width (E)
DEP-17-0663	7 5/8'' Reg	7 5/8'' Reg	Acc.	Acc.	Acc.	9 ½''	3 1/8''	5 ¼''	6 3/8''	1''	8 13/16''	9 ½''	7 1/16''	5/8''	5 7/8''	9 3/8''	8 13/16''	19 1/8''	23 ½''	24''	75 7/8''	8 ½''
Conclusion:		*17 ¼'' ROLLER REAMER Was Found “Acceptable” At The Time of Inspection Ready to Use.																				

Abbreviations :

OD Outside Diameter	ID Inside Diameter	SRG Stress Relief Groove	CB Counter Bore	BB Bore Back	FB Float Bore
φ Diameter	λ Length	σ Width	δ Depth	NP Not Present	NA Not Applicable
EGR Elevator Groove Recess	SGR Slip Groove Recess	CR Crack	B Bent	PC Premium Class	RF Reface
GT Galled Thread	TP Thread Pitting	SP Seal Pitting	TD Thread Damage	SD Seal Damage	M Mashed
1 100 % Coating	2 99-71 % Coating	3 70-40 % Coating	4 Up to 40 %	5 Nil	WT Wall Thickness
Colors Code:		Red Crack or Extreme Damage.	Blue Damage	Green Seal Damage	Yellow ACFM

Inspector	Review By					
Qualification:	Senior Inspector:	M.FAHAD	Supervisor:	WAQAS AWAN	Customer Name:	
Signature:					Customer Signature:	
Original - Client Files		Copy - Area Office		QC/FN/IBS/001 Rev.00		Dated: 07 Nov 2021

