

AI TAKAMUL COMPANY FOR ENGINEERING TESTS  
AND PROFESSIONAL SAFETY LIMITED

Basra, North Rumaila, Quality Control Yard - Iraq  
Tel: +9647810009138 / +9647834964657  
Email: [OP@qualitycontrol-iraq.com](mailto:OP@qualitycontrol-iraq.com) / [hany.akafi@qualitycontrol-iraq.com](mailto:hany.akafi@qualitycontrol-iraq.com)



INSPECTION CERTIFICATE OF 8 1/4" BALL CATCHER#WES825BP384

|                                                 |                                                                                        |                        |                                                                                                      |
|-------------------------------------------------|----------------------------------------------------------------------------------------|------------------------|------------------------------------------------------------------------------------------------------|
| Client Name:                                    | AL-ESNAAD OIL TOOL FOR OIL SERVICES.LLC                                                | Report No.:            | QC-24-05-AL-ESNAAD-050                                                                               |
| Acceptance criteria.                            | DS-1, Volume 4 Fifth Edition                                                           | Date of Inspection:    | 13.MAY.2024                                                                                          |
| Work Location:                                  | AL-ESNAAD OIL TOOL YARD                                                                | RIG NAME:              | AL-ESNAAD                                                                                            |
| TEST EQUIPMENT & CONSUMABLE DETAILS             |                                                                                        |                        |                                                                                                      |
| WHITE CONTRAST WCP-2                            | Batch #: 220602 Manufacture: Magnaflux<br>Exp Date: JUN,2025                           | TECHNICAL DETAILS      | Wet Visible Continuous                                                                               |
| BLACK INK 7HF                                   | Batch#: 220605 Manufacture: Magnaflux<br>Exp Date: JULY.2025                           | COIL(1200 AMP-TURNS/IN | SC 22713 Cal.15.FEB.2024<br>Cal Due14.AUG.2024                                                       |
| FLUORESCENT 14HF                                | Batch #: 220306 Manufacture: Magnaflux<br>Exp Date: March.2025                         | A.C HAND YOKE          | 201504053 Cal.15.FEB.2024<br>Cal Due14.AUG.2024                                                      |
| INTENSITY METER                                 | SR#1608000134 CAL.Date Cal. 15.FEB.2024<br>Cal Due 14.AUG.2024                         | UV BLACK LIGHT         | SR#1900084 Cal.15.FEB.2024<br>Cal Due14.AUG.2024                                                     |
| LEAD GAGE                                       | SR#AH07KF0027 GAEMAKER LG-5003<br>Cal. 13.FEB.2024<br>Cal Due 12.AUG.2024              | THREAD PROFILE GAGE    | SR#21336 Cal. 13.FEB.2024<br>Cal Due 12.AUG.2024<br>SR#21335 Cal. 15.FEB.2024<br>Cal Due 14.AUG.2024 |
| Magnetic Partical Concentration 7 HF            | 1.2 TO 2.4 ML/100 ML                                                                   | WMPT Light Intensity   | 3450 Lux                                                                                             |
| Magnetic particle concentration flourcent 14 HF | 0.1 TO 0.4 ML/100 ML                                                                   | UV LIGHT INTENSITY:    | 3000 μw/cm²                                                                                          |
| MAGNITISUM DIRECTION (LONGITUDENAL)             |                                                                                        |                        |                                                                                                      |
| METHODOLOGY:                                    | • Through Visual inspection<br>• Dimensional<br>•MPI inspection with Ultraviolet light |                        |                                                                                                      |

| Serial No.                                                                           | Description       | Connection                                                                      |              | Result Inspection |      |      | Dimensional 3 Inspection |        |           |           |           |             |        |            |          |          |          |             |             |             |               |
|--------------------------------------------------------------------------------------|-------------------|---------------------------------------------------------------------------------|--------------|-------------------|------|------|--------------------------|--------|-----------|-----------|-----------|-------------|--------|------------|----------|----------|----------|-------------|-------------|-------------|---------------|
|                                                                                      |                   | Pin                                                                             | Box          | Pin               | Box  | Body | OD(In)                   | ID(In) | SRG ϕ(In) | SRG Ϙ(In) | Pin λ(In) | Bevel ϕ(In) | Box    |            |          |          |          | Body        |             |             |               |
|                                                                                      |                   |                                                                                 |              |                   |      |      |                          |        |           |           |           |             | OD(In) | CB ϕ(In)   | CB δ(In) | BB ϕ(In) | BB δ(In) | Bevel ϕ(In) | Pin T λ(In) | Box T λ(In) | Overall λ(In) |
| WES825BP384                                                                          | 8 ¼" BALL CATCHER | 6<br>5/8"Reg                                                                    | 6<br>5/8"Reg | Acc.              | Acc. | Acc. | 8 ¼"                     | 3 ½"   | 5 3/8"    | 1"        | 5"        | 7 ½"        | 8 ¼"   | 6<br>1/16" | 5/8"     | -        | -        | 7 ½"        | -           | -           | 47"           |
|  |                   |                                                                                 |              |                   |      |      |                          |        |           |           |           |             |        |            |          |          |          |             |             |             |               |
| Conclusion:                                                                          |                   | ■ 8 ¼" BALL CATCHER was found "Acceptable At time of Inspection Ready For Use." |              |                   |      |      |                          |        |           |           |           |             |        |            |          |          |          |             |             |             |               |

Abbreviations :

|              |                        |           |                    |                          |                      |        |               |             |               |      |                |
|--------------|------------------------|-----------|--------------------|--------------------------|----------------------|--------|---------------|-------------|---------------|------|----------------|
| OD           | Outside Diameter       | ID        | Inside Diameter    | SRG                      | Stress Relief Groove | CB     | Counter Bore  | BB          | Bore Back     | FB   | Float Bore     |
| φ            | Diameter               | λ         | Length             | ⌀                        | Width                | δ      | Depth         | NP.         | Not Present   | NA.  | Not Applicable |
| EGR          | Elevator Groove Recess | SGR       | Slip Groove Recess | CR                       | Crack                | B      | Bent          | PC          | Premium Class | RF   | Reface         |
| GT           | Galled Thread          | TP        | Thread Pitting     | SP                       | Seal Pitting         | TD     | Thread Damage | SD          | Seal Damage   | M    | Mashed         |
| 1            | 100 % Coating          | 2         | 99-71 % Coating    | 3                        | 70-40 % Coating      | 4      | Up to 40 %    | 5           | Nil           | WT   | Wall Thickness |
| Colors Code: |                        | No Detect | Red                | Crack or Extreme Damage. | Blue                 | Damage | Green         | Seal Damage | Yellow        | ACFM |                |

|                         |                   |                    |                     |                    |                     |
|-------------------------|-------------------|--------------------|---------------------|--------------------|---------------------|
| Inspector Name:         | Review By         |                    |                     |                    |                     |
| Qualification:          | Senior Inspector: | M.FAHAD            | Supervisor:         | WAQAS AWAN         | Customer Name:      |
| Signature:              |                   |                    |                     |                    | Customer Signature: |
| Original - Client Files |                   | Copy - Area Office | QC/FN/FLS/03 Rev.00 | Dated: 07 Nov 2021 |                     |

