

AI TAKAMUL COMPANY FOR ENGINEERING TEST AND PROFESSIONAL SAFETY LIMITED

Basra, North Rumaila, Quality Control Yard - Iraq
Tel: +9647810009138 / +9647834964657




INSPECTION CERTIFICATE FOR 5" PUP JOINT

Client Name:	HALLIBURTON (HCT)	Report No.:	HAL-24-05-MS-HCT-2179
Acceptance criteria.	DS-1 Volume 3 Fifth Edition	Date of Inspection:	12.May.2024
Refrance Standard HCT	MAN-GL-HAL-HCT-900 REV NO.6.3	Next Inspection Date:	11.November 2024
		Halliburton Doc. (Visual Procedure D00305796 Revision U)	
Halliburton Doc. (Dimensional Procedure D00301932 Revision L)		Halliburton Doc. (MPI Procedure D00976850 Revision D)	
TEST EQUIPMENT & CONSUMABLE DETAILS			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN,2025	TECHNICAL DETAILS	Wet Visible Continuous
BLACK INK 7HF	Batch#: 220605 Manufacture: Magnaflux Exp Date: JULY.2025	COIL(1200 AMP-TURNS/IN	SR#22650 Cal.13.FEB.2024 Cal Due 12.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March.2025	A.C HAND YOKE	SR#201504052 Cal.13.FEB.2024 Cal Due 12.AUG.2024
INTENSITY METER	SR#R.043943 Cal.13.FEB.2024 Cal Due 12.AUG.2024	UV BLACK LIGHT	SR#1898977 Cal.13.FEB.2024 Cal Due 12.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 Cal.13.FEB.2024 Cal Due 12.AUG.2024	THREAD PROFILE GAGE	SR#21336 CAL.Date. Cal.13.FEB.2024 Cal Due 12.AUG.2024 SR#21335 CAL.Date. Cal.15.FEB.2024 Cal Due 14.AUG.2024
Magnetic Partical Concentration 7 HF	1.2 TO 2.4 ML/100 ML	UV LIGHT INTENSITY:	3120 μw/cm²
Magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	WMPT Light Intensity:	3610 Lux
MAGNITISUM DIRECTION (LONGITUDENAL)			
METHODOLOGY:	•Through Visual inspection • Dimensional Inspection •MPI inspection with Ultraviolet light		

Serial No.	Description	Connection		Result Inspection			Dimensional Inspection														
		Pin	Box	Pin	Box	Body	Pin					Box					Body				
							OD(In)	ID(In)	Neck ϖ (In)	Pin λ (In)	Bevel ϕ (In)	OD(In)	CB ϕ (In)	CB δ (In)	BB ϕ (In)	BB δ (In)	Bevel ϕ (In)	Pin T λ (In)	Box T λ (In)	Overall λ (In)	
HCT-PJ-006	5" PUP JOINT	4 1/2 IF	4 1/2 IF	Acc.	Acc.	Acc.	7"	3 1/4"	12/32"	4 1/2"	6 2/32"	7"	5 10/32"	5/8"	-	-	6 2/32"	8"	9 5/8"	90 9/16"	
																					
Conclusion:		■ 01 PUP JOINT was found "Acceptable". At time of Inspection Ready For Use.																			

Abbreviations :

OD	Outside Diameter	ID	Inside Diameter	SRG	Stress Relief Groove	CB	Counter Bore	BB	Bore Back	FB	Float Bore
ϕ	Diameter	λ	Length	ϖ	Width	δ	Depth	NP.	Not Present	NA.	Not Applicable
EGR	Elevator Groove Recess	SGR	Slip Groove Recess	CR	Crack	B	Bent	PC	Premium Class	RF	Reface
GT	Galled Thread	TP	Thread Pitting	SP	Seal Pitting	TD	Thread Damage	SD	Seal Damage	M	Mashed
1	100 % Coating	2	99-71 % Coating	3	70-40 % Coating	4	Up to 40 %	5	Nil	WT	Wall Thickness
Colors Code:		White	No Defects	Red	Crack or Extreme Damage.	Blue	Damage	Green	Seal Damage	Yellow	ACFM

Inspector Name:	M.Shanzad Ahmed	Review By					
Qualification:	ASNT Level II (MT/PT/ET)	Senior Inspector:	NAVEED HUSSAIN	Supervisor:	Hani Ali	Customer Name:	
Signature:						Customer Signature:	
Original - Client Files		Copy - Area Office	QC/FN/FLS/03 Rev.00	Dated: 07 Nov 2021			

