

AI TAKAMUL COMPANY FOR ENGINEERING TESTS AND PROFESSIONAL SAFETY LIMITED

Basra, North Rumaila, Quality Control Yard - Iraq

Tel: +9647810009138 / +9647834964657

Email: OP@qualitycontrol-iraq.com / hany.akafi@qualitycontrol-iraq.com



CERTIFICATE OF INSPECTION FOR 5" HWDP

Client Name:	DAQING DRILLING	Report No.:	DQ-22-QC-24-06-RS-001
Acceptance Creater:	DS-1 Fifth Edition, Volume 3 CAT 3-5	Date of Inspection:	10.JUNE.2024
Work Location:	RU-618	Rig No.:	DQ-22
Test Equipment & Consumable Details			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN,2025	TECHNICAL DETAILS	Wet Visible Continuous
BLACK INK 7HF	Batch#: 220605 Manufacture: Magnaflux Exp Date: JULY.2025	COIL(1200 AMP-TURNS/IN	SC 22713 Cal.15.FEB.2024 Cal Due14.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March.2025	A.C HAND YOKE	201504053 Cal.15.FEB.2024 Cal Due14.AUG.2024
INTENSITY METER	SR#160800134 CAL.Date Cal. 15.FEB.2024 Cal Due 14.AUG.2024	UV BLACK LIGHT	SR#1900084 Cal.15.FEB.2024 Cal Due14.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 Cal. 13.FEB.2024 Cal Due 12.AUG.2024	THREAD PROFILE GAGE	SR#21336 Cal. 13.FEB.2024 Cal Due 12.AUG.2024 SR#21335 Cal. 15.FEB.2024 Cal Due 14.AUG.2024
Magnetic Partical Concentration 7 HF	1.2 TO 2.4 ML/100 ML	WMPT Light Intensity	3450 Lux
Magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	UV LIGHT INTENSITY:	2900 µw/cm ²
Magnetism Direction (Longitudinal)			
METHODOLOGY:	Through Visual inspection • Dimensional	•MPI inspection with Ultraviolet light Heat Checking Thread Profile Gauging.	
Connection:	NC50	Size:	5"

Serial No.	Visual Inspection				Black Light		Dimensional 3 Inspection															
							Pin						Box						Body			
	Pin	Box	Body	HB	Pin	Box	OD (in)	ID (in)	SRG ϕ (in)	SRG λ (in)	Bevel ϕ (in)	pinλ (in)	OD (in)	CB ϕ (in)	CB δ (in)	BB ϕ (in)	BB δ (in)	Bevel ϕ (in)	Seal ϖ	Pin Tong λ (in)	Box Tong λ (in)	Center Post ϕ (in)
145115	Acc	Acc	Acc	√	Acc	Acc	6 5/8"	3 1/16"	4 23/32"	13/16"	6 1/16"	4 7/16"	6 5/8"	5 5/16"	5/8"	4 5/8"	7 7/8"	6 1/16"	14/32"	15 1/2"	19 1/8"	5 1/2"
37-10	Acc	Acc	Acc	√	Acc	Acc	6 5/8"	3 1/16"	4 23/32"	3/4"	6 1/16"	4 7/16"	6 5/8"	5 5/16"	5/8"	4 5/8"	8"	6 1/16"	14/32"	15 3/8"	19 7/8"	5 1/2"
106000912	Acc	Acc	Acc	√	Acc	Acc	6 5/8"	3 1/16"	4 23/32"	3/4"	6 1/16"	4 7/16"	6 5/8"	5 5/16"	5/8"	4 5/8"	7 7/8"	6 1/16"	14/32"	12 1/4"	19 1/2"	5 1/2"
2932	Acc	Acc	Acc	√	Acc	Acc	6 5/8"	3 1/16"	4 23/32"	3/4"	6 1/16"	4 7/16"	6 5/8"	5 5/16"	5/8"	4 5/8"	8 1/8"	6 1/16"	14/32"	15 1/2"	16 1/2"	5 1/2"
106000903	Acc	Acc	Acc	√	Acc	Acc	6 5/8"	3 1/16"	4 23/32"	15/16"	6 1/16"	4 7/16"	6 5/8"	5 5/16"	5/8"	4 5/8"	7 7/8"	6 1/16"	14/32"	18"	16 1/4"	5 1/2"
Conclusion:	The Above Mentioned 5" Heavy Weight Drill Pipe was Found Acceptable from at time of Inspection ready to use.																					

Abbreviations :

OD	Outside Diameter	ID	Inside Diameter	SRG	Stress Relief Groove	CB	Counter Bore	BB	Bore Back	FB	Float Bore
ϕ	Diameter	λ	Length	ϖ	Width	δ	Depth	NP.	Not Present	NA.	Not Applicable
EGR	Elevator Groove Recess	SGR	Slip Groove Recess	CR	Crack	B	Bent	PC	Premium Class	RF	Reface
GT	Galled Thread	TP	Thread Pitting	SP	Seal Pitting	TD	Thread Damage	SD	Seal Damage	M	Mashed
1	100 % Coating	2	99-71 % Coating	3	70-40 % Coating	4	Up to 40 %	5	Nil	WT	Wall Thickness
Colors Code:		White	No Defects	Red	Crack or Extreme	Blue	Damage	Green	Seal Damage	Yellow	ACFM

Inspector Name:	.FAHAD		Review By	
Qualification:	Senior Inspector:	Supervisor:	Customer Name:	
Signature:		WAQAS	Customer Signature:	

Original - Client Files

Copy - Area Office

QC/FN/DJ-PB/029

Rev.00 dated 07.Nov2021

