

AI TAKAMUL COMPANY FOR ENGINEERING TESTS AND PROFESSIONAL SAFETY LIMITED

Basra, North Rumaila, Quality Control Yard - Iraq

Tel: +9647810009138 / +9647834964657

/ hany.akafi@qualitycontrol-iraq.com OP@qualitycontrol-iraq.com Email:



INSPECTION CERTIFICATE OF 8 1/4" BALL CATCHER#SBM825BP99

Client Name:	AL-ESNAAD OIL TOOL FOR OIL SERVICES.LLC	Report No.:	QC-06-24-0180-10
Acceptance criteria:	DS-1, Volume 4 Fifth Edition	Date of Inspection:	14,June2024
Work Location:	AL-ESNAAD OIL TOOL FOR OIL SERVICES.LLC	RIG NAME:	AL-ESNAAD
TEST EQUIPMENT & CONSUMABLE DETAILS			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN,2025	TECHNICAL DETAILS	Wet Visible Continuous
BLACK INK 7HF	Batch#.220605 Manufacture: Magnaflux Exp Date: JULY,2025	COIL(1200 AMP-TURNS)/IN	SC 22713 Cal.15.FEB.2024 Cal Due14.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March,2025	A.C HAND YOKE	201504053 Cal.15.FEB.2024 Cal Due14.AUG.2024
INTENSITY METER	SR#1608000134 CAL.Date Cal. 15.FEB.2024 Cal Due 14.AUG.2024	UV BLACK LIGHT	SR#1900084 Cal.15.FEB.2024 Cal Due14.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 Cal. 13.FEB.2024 Cal Due 12.AUG.2024	THREAD PROFILE GAGE	SR#21336 Cal. 13.FEB.2024 Cal Due 12.AUG.2024 SR#21335 Cal. 15.FEB.2024 Cal Due 14.AUG.2024
Magnetic Partical Concentration 7 HF	1.2 TO 2.4 ML/100 ML	WMPT Light Intensity	3450 Lux
Magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	UV LIGHT INTENSITY:	3030 μw/cm ²
MAGNITISUM DIRECTION (LONGITUDENAL)			
METHODOLOGY:	<ul style="list-style-type: none"> • Through Visual inspection • Dimensional • MPI inspection with Ultraviolet light 		

Serial No.	Description	Connection		Result Inspection			Dimensional 3 Inspection														
		Pin	Box	Pin	Box	Body	Pin					Box				Body					
							OD(In)	ID(In)	SRG φ(In)	SRG ⌀ (In)	Pin λ(In)	Bevel φ(In)	OD(In)	CB φ(In)	CB δ(In)	BB φ(In)	BB δ(In)	Bevel φ(In)	Pin T λ(In)	Box T λ(In)	Overall λ(In)
SBM825BP99	8 1/4" BALL CATCHER	6 5/8 R	6 5/8 R	Acc.	Acc.	Acc.	8 1/4"	3 1/2"	5 3/8"	7/8"	5"	7 11/16"	8 1/4"	6 1/16"	5/8"	--	--	7 11/16"	--	--	51 3/4"



Conclusion: ■ 8 1/4" BALL CATCHER Was Found Acceptable At time of Inspection Ready For Use.

Abbreviations :

OD Outside Diameter	ID Inside Diameter	SRG Stress Relief Groove	CB Counter Bore	BB Bore Back	FB Float Bore
φ Diameter	λ Length	⌀ Width	δ Depth	NP. Not Present	NA. Not Applicable
EGR Elevator Groove Recess	SGR Slip Groove Recess	CR Crack	B Bent	PC Premium Class	RF Reface
GT Galled Thread	TP Thread Pitting	SP Seal Pitting	TD Thread Damage	SD Seal Damage	M Mashed
1 100 % Coating	2 99-71 % Coating	3 70-40 % Coating	4 Up to 40 %	5 Nil	WT Wall Thickness
Colors Code:	White No Defects	Red Crack or Extreme Damage.	Blue Damage	Green Seal Damage	Yellow ACFM

Inspector	M.SARWAR	Review By					
Qualification:	ASNT Level II (MT, ET, VT)	Senior Inspector:	RAO SHAIL	Supervisor:	NAVEED	Customer Name:	
Signature:						Customer Signature:	

Original - Client Files

Copy - Area Office

QC/FN/FLS/03 Rev.00

Dated: 07 Nov 2021

