

## Calibration Certificate

Al Takamul Yard, North Rumailah Iraq

• Phone : +964 7810009138 • www.qualitycontrol-iraq • E-mail: op@qualitycontrol-iraq

Date of Issue: June 3, 2024

Page 1 of 1

REQUEST NUMBER : By Mail	CUSTOMERS DETAILS
QC JOB NUMBER : QC/JN/24/00226	Name : Halliburton Worldwide-Iraq Branch (Sperry)
CERTIFICATE NUMBER : QC240603-09	Address : Oil Street, Western Burjessia Basra South Iraq

### EQUIPMENT IDENTIFICATION AND SPECIFICATIONS

Description	Torque Wrench	Calibration Date	: June 3, 2024
Type of Indication	Analog	Calibration Due	: June 2, 2025
Manufacturer	: PROTO	Last Calibration	: June 20, 2023
Model	: 6012C		
Serial Number	: DLA38806		
SAP No.	: 300198922		
Calibrated Range	: 20 to 100 LB.FT		
Resolution	: 0.5 LB.FT		
Tolerance	: $\pm 4\%$		
As Found	: In Tolerance		



### ENVIRONMENTAL CONDITIONS DURING TEST

Ambient Temperature	: 22 °C	$\pm$	2°C	Relative Humidity	: 45 %RH	$\pm$	5% RH
---------------------	---------	-------	-----	-------------------	----------	-------	-------

### CALIBRATION METHOD

The above equipment has been calibrated in accordance with International Calibration standard # ISO 6789-1:2017

The deviations of the measurements obtained from UUC with respect to reference standards are determined to obtain the error.

### REFERENCE EQUIPMENT USED :

DESCRIPTION	MAKE / MODEL	SERIAL #	CALIBRATION DATE	CALIBRATION DUE DATE
Torque Wrench Calibrator	Nobar / Pro Test 1500	90962	20 Nov, 2023	19 Nov, 2024

### CALIBRATION TEST RESULTS

#### Measurement Data For Torque

#### Clockwise Measurements

Readings on UUC	Readings on Ref. Standard (Avg. of 5 Measurements)	Deviation	Error Percentage (Tolerance $\pm 4\%$ )	Uncertainty (95 % C.L)
LB.FT	LB.FT	LB.FT	%	$\pm$ LB.FT
20.0	20.50	-0.50	-0.5	0.30
60.0	61.30	-1.30	-1.3	0.30
100.0	101.50	-1.50	-1.5	0.30
Counter Clockwise Measurements				
20.0	20.80	-0.80	-0.8	0.30
60.0	62.30	-2.30	-2.3	0.30
100.0	101.80	-1.80	-1.8	0.30

Calibration results were found to conform as per specified accuracy requirements. Above Instrument has **PASSED** its Calibration.

The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor  $k=2$ , providing a level of confidence of approximately 95%. The uncertainty evaluation has been carried out in accordance with international practice.

DEVIATION FROM STANDARD METHOD : None

REMARK (S) : ☒ The results are as found (no adjustment done).  
☐ The results are post adjustment.

CALIBRATED BY	REVIEWED & APPROVED BY LAB INCHARGE	CLIENT
 Mahdi Halim	 LAB INCHARGE Asjad Rafid	