



### CERTIFICATE OF INSPECTION FOR 8" DRILL COLLAR

<b>Client Name:</b>	<b>DAQING DRILLING</b>	<b>Report No.:</b>	DQ-12-QC-7-24-0213-002
<b>Acceptance Creater:</b>	DS-1 Fifth Edition, Volume 3 CAT 3-5	<b>Date of Inspection:</b>	25.JULY.2024
<b>Work Location:</b>	R-814	<b>Rig No.:</b>	DQ-12
<b>Test Equipment &amp; Consumeable Details</b>			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN.2025	TECHNICAL DETAILS	Wet Visible Continuous
BLACK INK 7HF	Batch#: 220605 Manufacture: Magnaflux Exp Date: JULY.2025	COIL(1200 AMP-TURNS/IN	SC 22713 Cal.15.FEB.2024 Cal Due14.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March.2025	A.C HAND YOKE	201504053 Cal.15.FEB.2024 Cal Due14.AUG.2024
INTENSITY METER	SR#160800134 CAL.Date Cal. 15.FEB.2024 Cal Due 14.AUG.2024	UV BLACK LIGHT	SR#1900084 Cal.15.FEB.2024 Cal Due14.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 Cal. 13.FEB.2024 Cal Due 12.AUG.2024	THREAD PROFILE GAGE	SR#21336 Cal. 13.FEB.2024 Cal Due 12.AUG.2024 SR#21335 Cal. 15.FEB.2024 Cal Due 14.AUG.2024
Magnetic Partical Concentration 7 HF	1.2 TO 2.4 ML/100 ML	WMPT Light Intensity	3500 Lux
Magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	UV LIGHT INTENSITY:	3050 µw/cm <sup>2</sup>
Magnetism Direction (Longitudinal)			
METHODOLOGY:	• Through Visual inspection      •MPI inspection with Ultraviolet light • Dimensional 3		
<b>Connection:</b>	<b>6 5/8 REG</b>	<b>Size:</b>	<b>8"</b>

Serial No.	Visual Inspection			MPI			Dimensional 3 Inspection																
	Pin	Box	Body	Pin	Box	Body	Pin					Box					Body						
							OD (in)	ID (in)	SRG (in)	SRG W (in)	Pin (in)	Bevel (in)	OD (in)	CBD (in)	CBW (in)	BB (in)	BBL (in)	Bevel (in)	Pin Tong (in)	Box Tong (in)	EGR (in)	SGR (in)	Overall (in)
DQ-007	Acc.	GT/SD.	Acc.	Acc.	Acc.	Acc.	8 1/16"	2 7/8"	5 3/8"	13/16"	4 15/16"	7 9/16"	8 1/16"	6 1/16"	5/8"	5 18/64"	8 1/2"	7 9/16"	7 1/4"	17 1/2"	5/16"	7/32"	363 3/4"
DQ-004	Acc.	TD/SD	Acc.	Acc.	Acc.	Acc.	8"	2 7/8"	5 3/8"	13/16"	5"	7 1/2"	8 1/16"	6 1/16"	5/8"	5 18/64"	8 5/16"	7 1/2"	24 7/8"	14"	5/16"	7/32"	358"
D-33	Acc.	TD/SD	Acc.	Acc.	Acc.	Acc.	8 1/16"	2 7/8"	5 3/8"	13/16"	4 15/16"	7 9/16"	8 1/16"	6 1/16"	5/8"	5 18/64"	8 1/4"	7 9/16"	22 1/4"	13 3/4"	5/16"	7/32"	368 1/4"
--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

**Conclusion:** ■ 03 DRILL COLLARS above were found BOX SIDE Rejected. At the time of Inspection Need to Be Repaired

**Abbreviations :**

<b>OD</b> Outside Diameter	<b>ID</b> Inside Diameter	<b>SRG</b> Stress Relief Groove	<b>CB</b> Counter Bore	<b>BB</b> Bore Back	<b>FB</b> Float Bore
☐ Diameter	☐ Length	☐ Width	☐ Depth	<b>NP.</b> Not Present	<b>NA.</b> Not Applicable
<b>EGR</b> Elevator Groove Recess	<b>SGR</b> Slip Groove Recess	<b>CR</b> Crack	<b>B</b> Bent	<b>PC</b> Premium Class	<b>RF</b> Reface
<b>GT</b> Galled Thread	<b>PT</b> Pitting Thread	<b>SP</b> Seal Pitting	<b>TD</b> Thread Damage	<b>SD</b> Seal Damage	<b>M</b> Mashed
<b>1</b> 100 % Coating	<b>2</b> 99-71 % Coating	<b>3</b> 70-40 % Coating	<b>4</b> Up to 40 %	<b>5</b> Nil	<b>WT</b> Wall Thickness
<b>Colors Code:</b>		<b>White</b> No Defects	<b>Red</b> Crack or Extreme Damage.	<b>Blue</b> Damage	<b>Green</b> Seal Damage <b>Yellow</b> ACFM

<b>Inspector Name:</b>	M.SARWAR	<b>Review By</b>			
<b>Qualification:</b>	Senior Inspector:	RAO SOHAIL	Supervisor:	NAVEED HUSSAIN	Customer Name:
<b>Signature:</b>					Customer Signature:

Original - Client Files      Copy - Area Office      QC/FN/AF,REP/026 Rev.00 Dated 01 AUG 2021

