



11 3/4" STRING STABILIZER INSPECTION CERTIFICATE

Client Name:	ZHONGMAN PETROLEUM ENGINEERING TECHNOLOGY (HONG KONG) CO LIMITED IRAQ	Report No.:	ZPEC-16-QC-24-08-RS-014
Acceptance criteria:	DS-1 Fifth Edition, Volume 3 CAT 3-5	Date of Inspection:	07.AUG.2024
Work Location:	PO-64		
RIG NAME:	ZPEC-16(DD)		
TEST EQUIPMENT & CONSUMABLE DETAILS			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN,2025	TECHNICAL DETAILS	Wet Visible Continuous
BLACK INK 7HF	Batch#: 220605 Manufacture: Magnaflux Exp Date: JULY.2025	COIL(1200 AMP-TURNS/IN	SC 22713 Cal.15.FEB.2024 Cal Due 14.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March.2025	A.C HAND YOKE	201504053 Cal.15.FEB.2024 Cal Due 14.AUG.2024
INTENSITY METER	SR#1608000134 CAL.Date Cal. 15.FEB.2024 Cal Due 14.AUG.2024	UV BLACK LIGHT	SR#1900084 Cal.15.FEB.2024 Cal Due 14.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 Cal. 13.FEB.2024 Cal Due 12.AUG.2024	THREAD PROFILE GAGE	SR#21336 Cal. 13.FEB.2024 Cal Due 12.AUG.2024
Magnetic Partical Concentration 7HF	1.2 TO 2.4 ML/100 ML		SR#21335 Cal. 15.FEB.2024 Cal Due 14.AUG.2024
magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	WMPT Light Intensity	3500 Lux
RING GAUGE	DES11 3/4" RING GAUGE SR # RGB-003(M/NO343-140) CAL.Date.04.SEP.2023 CAL Due Date. 03.SEP.2024	UV LIGHT INTENSITY:	3050 μw/cm ²

MAGNITISUM DIRECTION (LONGITUDENAL)

METHODOLOGY:	<ul style="list-style-type: none"> Through Visual inspection Dimensional 3 	<ul style="list-style-type: none"> MPI inspection with Ultraviolet light
---------------------	--	---

STRING STABILIZER	
11 3/4"	

Serial No.	Connection		Condition			Dimensional 3 Inspection																
	Pin	Box	Pin	Box	Body	Pin					Box					Body						
						OD	ID (F)	PIN λ(In)	SRG φ	SRG λ(In)	BEVEL φ	OD	CB φ	CB λ(In)	BBφ	BBλ(In)	BEVEL φ	Fishing Neck (A)	Blade Length (B)	Down Length (C)	Overall Length(D) (In)	Blade Width (E)
2018-12-(43132)	6 5/8 REG	6 5/8 REG	Acc.	Acc.	Acc.	8"	2 7/8"	4 15/16"	5 3/8"	3/4"	7 11/16"	8"	6 2/32"	5/8"	5 18/64"	8 3/4"	7 11/16"	24 7/8"	22 1/2"	19 1/4"	69 3/4"	3 1/2"

Conclusion: *11 3/4" String Stabilizers Was Found "Acceptable" At The Time of Inspection Ready to Use.

Abbreviations :

OD Outside Diameter	ID Inside Diameter	SRG Stress Relief Groove	CB Counter Bore	BB Bore Back	FB Float Bore
φ Diameter	λ Length	ω Width	δ Depth	NP. Not Present	NA. Not Applicable
EGR Elevator Groove Recess	SGR Slip Groove Recess	CR Crack	B Bent	PC Premium Class	RF Reface
GT Galled Thread	TP Thread Pitting	SP Seal Pitting	TD Thread Damage	SD Seal Damage	M Mashed
1 100 % Coating	2 99-71 % Coating	3 70-40 % Coating	4 Up to 40 %	5 Nil	WT Wall Thickness
Colors Code:		Red Crack or Extreme Damage.	Blue Damage	Green Seal Damage	Yellow ACFM

Inspector:	M.USMAN			Review By:	M.SARWAR		
Qualification:	Senior Inspector		Supervisor	Customer Name:			
Signature:				Customer Signature:			

Original - Client Files Copy - Area Office QC/FN/IBS/001 Rev.00 Dated: 07 Nov 2021

