

**AI TAKAMUL COMPANY FOR ENGINEERING TESTS AND PROFESSIONAL SAFETY LIMITED**

Basra, North Rumaila, Quality Control Yard - Iraq

Tel: +9647810009138 / +9647834964657

Email: [OP@qualitycontrol-iraq.com](mailto:OP@qualitycontrol-iraq.com) / [hany.akafi@qualitycontrol-iraq.com](mailto:hany.akafi@qualitycontrol-iraq.com)



**INSPECTION CERTIFICATE OF BOTTEL NECK X-OVER# 7767**

<b>Client Name:</b>	<b>DAQING DRILLING</b>	<b>Report No.:</b>	DQ-1202-QC-24-08-RS-028
<b>Acceptance Criteria:</b>	DS-1 Fifth Edition, Volume 3	<b>Date of Inspection:</b>	8.AUG.2024
<b>Work Location:</b>	(R-816)	<b>Rig No.:</b>	DQ-1202
<b>TEST EQUIPMENT &amp; CONSUMABLE DETAILS</b>			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN,2025	<b>TECHNICAL DETAILS</b>	Wet Visible Continuous
BLACK INK 7HF	Batch#:220605 Manufacture: Magnaflux Exp Date: JULY.2025	COIL(1200 AMP-TURNS/IN	SC 22713 Cal.15.FEB.2024 Cal Due 14.AUG.2024
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March.2025	A.C HAND YOKE	201504053 Cal.15.FEB.2024 Cal Due 14.AUG.2024
INTENSITY METER	SR#1608000134 CAL.Date Cal. 15.FEB.2024 Cal Due 14.AUG.2024	UV BLACK LIGHT	SR#1900084 Cal.15.FEB.2024 Cal Due 14.AUG.2024
LEAD GAGE	SR#AH07KF0027 GAEMAKER LG-5003 Cal. 13.FEB.2024 Cal Due 12.AUG.2024	THREAD PROFILE GAGE	SR#21336 Cal. 13.FEB.2024 Cal Due 12.AUG.2024 SR#21335 Cal. 15.FEB.2024 Cal Due 14.AUG.2024
Magnetic Partical Concentration 7 HF	1.2 TO 2.4 ML/100 ML	WMPT Light Intensity	3500 Lux
Magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	UV LIGHT INTENSITY:	3050µw/cm <sup>2</sup>
Magnetism Direction (Longitudinal)			
<b>METHODOLOGY:</b>	<ul style="list-style-type: none"> <li>• Through Visual inspection</li> <li>• Dimensional 3</li> <li>• MPI inspection with Ultraviolet light</li> </ul>		

Serial No.	Description	Connection		Result Inspection			Dimensional 3- Inspection														
		Pin	Box	Pin	Box	Body	Pin					Box					Body				
							OD(In)	ID(In)	SRG (In)	SRGW (In)	Pin (In)	Bevel (In)	OD(In)	CB (In)	CB (In)	BB (In)	BBL (In)	Bevel (In)	Tongspac e (In)	Box Lth (In)	Overall (In)
7767	BOTTEL NECK X-OVER	6 5/8Reg	NC-50	Acc.	Acc.	Acc.	8 1/8"	2 3/4"	5 13/32"	3/4"	5"	7 13/16"	6 3/4"	5 5/16"	5/8"	4 40/64"	8 1/16"	6 1/2"	8 1/8"	18 3/8"	43 1/4"

**Conclusion :** \*01 BOTTEL NECK X-OVER above was found "Acceptable". At the time of Inspection (Ready for Use).

<b>OD</b> Outside Diameter	<b>ID</b> Inside Diameter	<b>SRG</b> Stress Relief Groove	<b>CB</b> Counter Bore	<b>BB</b> Bore Back	<b>FB</b> Float Bore
⊠ Diameter	⊠ Length	⊠ Width	⊠ Depth	<b>NP.</b> Not Present	<b>NA.</b> Not Applicable
<b>EGR</b> Elevator Groove Recess	<b>SGR</b> Slip Groove Recess	<b>CR</b> Crack	<b>B</b> Bent	<b>PC</b> Premium Class	<b>RF</b> Reface
<b>GT</b> Galled Thread	<b>PT</b> Pitting Thread	<b>SP</b> Seal Pitting	<b>TD</b> Thread Damage	<b>SD</b> Seal Damage	<b>M</b> Mashed
<b>1</b> 100 % Coating	<b>2</b> 99-71 % Coating	<b>3</b> 70-40 % Coating	<b>4</b> Up to 40 %	<b>5</b> Nil	<b>WT</b> Wall Thickness
<b>Colors Code:</b> <span style="background-color: #d3d3d3; padding: 2px;">White</span> No Defects		<span style="background-color: #ff0000; padding: 2px;">Red</span> Crack or Extreme Damage.	<span style="background-color: #0000ff; padding: 2px;">Blue</span> Damage	<span style="background-color: #008000; padding: 2px;">Green</span> Seal Damage	<span style="background-color: #ffff00; padding: 2px;">Yellow</span> ACFM

<b>Inspector Name:</b>	USMAN SHABBIR	<b>Review By</b>			
<b>Qualification:</b>	Senior Inspector	<b>Customer Name:</b>			
<b>Signature:</b>	NAVEED HUSSAIN	<b>Supervisor:</b>	RAO SOHAIL	<b>Customer Signature:</b>	

Original - Client Files      Copy - Area Office      QC/FN/AF,REP/026 Rev.00 Dated 01 AUG 2021

