

AI TAKAMUL COMPANY FOR ENGINEERING TESTS AND PROFESSIONAL SAFETY LIMITED

Basra, North Rumaila, Quality Control Yard - Iraq

Tel: +9647810009138 / +9647834964657

Email: OP@qualitycontrol-iraq.com / hany.akafi@qualitycontrol-iraq.com



AFTER REPAIR INSPECTION CERTIFICATE OF 5 1/2" HWDP

Client Name:	DAQING DRILLING	Report No.:	QC-24-10-DQ-1202-009
Acceptance Criteria:	<input checked="" type="checkbox"/> API SPEC 7-2	Date Of Inspection:	18.OCT.2024
Work Location:	ABERDEEN WORKSHOP	Rig Name	DQ-1202
Test Equipment & Consumeable Details			
WHITE CONTRAST WCP-2	Batch #: 220602 Manufacture: Magnaflux Exp Date: JUN,2025	TECHNICAL DETAILS	Wet Visible Continuous
BLACK INK 7HF	Batch#: 220605 Manufacture: Magnaflux Exp Date: JULY.2025	COIL(1200 AMP-TURNS/IN	22713 Cal.25.JUL.2024 Cal Due24.FEB.2025
FLUORESCENT 14HF	Batch #: 220306 Manufacture: Magnaflux Exp Date: March.2025	A.C HAND YOKE	PY-10 Cal.25.JUL.2024 Cal Due24.FEB.2025
INTENSITY METER	SR#1608000134 CAL.Date Cal. 25 JUL.2024 Cal Due 24.FEB.2025	UV BLACK LIGHT	SR#1895313 Cal.25.JUL.2024 Cal Due24.FEB.2025
LEAD GAGE	SR#AH07KF0026 GAEMAKER LG- Cal. 25.JUL.2024 Cal Due 24.FEB.2025	THREAD PROFILE GAGE	SR#21336 Cal. Cal.25.JUL.2024 Cal Due24.FEB.2025 SR#21335 Cal. Cal.25.JUL.2024 Cal Due24.FEB.2025
Magnetic Partical Concentration 7 HF	1.2 TO 2.4 ML/100 ML	WMPT Light Intensity	3520 Lux
Magnetic particle concentration flourcent 14 HF	0.1 TO 0.4 ML/100 ML	UV LIGHT INTENSITY:	2950 μw/cm ²
Magnetism Direction (Longitudinal)			
METHODOLOGY:	<ul style="list-style-type: none"> • Through Visual inspection • MPI inspection with Ultraviolet lig • Dimensional Inspection *Lead Gaiging, & Thread Profile Gaiging. 		
Connection:	5 1/2"FH	Size:	5 1/2"

Serial No.	Visual Inspection			Black Light		Dimensional 3 Inspection															
	Pin	Box	Body	Pin	Box	Pin					Box					Body					
						OD (in)	ID (in)	SRG DIA (in)	SRG (in)	Bevel (in)	pin (in)	OD (in)	CB (in)	CB (in)	BB (in)	BB (in)	Bevel (in)	Pin Tong (in)	Box Tong (in)	C.W Pad OD(in)	length (in)
2309753	-	Acc	-	-	Acc	-	-	-	-	-	-	7"	5 29/32"	5/8"	5 7/64"	8 1/2"	6 3/4"	-	-22 7/8"	-	-

Conclusion : The Above Mentioned 5 1/2" Heavy Weight Drill Pipe Were Found Acceptable from Box Connection After Repair at the time of Inspection, Ready to use.

Abbreviations :

OD Outside Diameter	ID Inside Diameter	SRG Stress Relief Groove	CB Counter Bore	BB Bore Back	FB Float Bore
EGR Elevator Groove Recess	SGR Slip Groove Recess	CR Crack	B Bent	PC Premium Class	RF Reface
GT Galled Thread	TP Thread Pitting	SP Seal Pitting	TD Thread Damage	SD Seal Damage	M Mashed
1 100 % Coating	2 99-71 % Coating	3 70-40 % Coating	4 Up to 40 %	5 Nil	WT Wall Thickness
Colors Code:					
White	No Defects	Red	Crack or Extreme Damage.	Blue	Damage
				Green	Seal Damage
				Yellow	ACFM

Inspector Name:		Review By			
Qualification:		Senior Inspector:	M.SARWAR	Supervisor:	AHMED MOHAMMED
Signature:					
		Customer Name:		Customer Signature:	

Original – Client Files Copy - Area Office QC/FN/DPI/NDT/006 Rev.00 DATED 07.NOV.2021

