

Certificate of Hydro Test

Al Takamul Yard, North Rumailah South Iraq

• Phone : +964 7810009138 • www.qualitycontrol-iraq.com • E-mail: op@qualitycontrol-iraq.com

Coustmer	: Black Gold Gulf, Basra, South Iraq	Job Number	: QC-YB-240051
Description	: Refillable Seamless Steel Gas Cylinders	Certificate No.	: QC-YB-240051-13
Cylinder Type	: NITROGEN N2	Temperature	: 22 ± 2°C
Manufacturer	: SHANDONG BEE GAS ENERGY TECH CO., LTD	Humidity	: 25 ± 5 % RH
Volumetric Capacity (L)	: 40.4 ± 0.1 L	Ref. Standard	: ISO 7866:2012

No.	Serial No.	Working Pressure (Bar)	Test Pressure (Bar)	Holding Time (m)	Hydro test date	Expired date
1	011	150.0	225.0	15 min	2024.11.15	2029.11.14
2	054	150.0	225.0	15 min	2024.11.15	2029.11.14
3	057	150.0	225.0	15 min	2024.11.15	2029.11.14
4	016	150.0	225.0	15 min	2024.11.15	2029.11.14
5	031	150.0	225.0	15 min	2024.11.15	2029.11.14
6	019	150.0	225.0	15 min	2024.11.15	2029.11.14
7	037	150.0	225.0	15 min	2024.11.15	2029.11.14
8	069	150.0	225.0	15 min	2024.11.15	2029.11.14
9	068	150.0	225.0	15 min	2024.11.15	2029.11.14
10	064	150.0	225.0	15 min	2024.11.15	2029.11.14
11	012	150.0	225.0	15 min	2024.11.15	2029.11.14
12	070	150.0	225.0	15 min	2024.11.15	2029.11.14
13	040	150.0	225.0	15 min	2024.11.15	2029.11.14
14	033	150.0	225.0	15 min	2024.11.15	2029.11.14
15	027	150.0	225.0	15 min	2024.11.15	2029.11.14
16	062	150.0	225.0	15 min	2024.11.15	2029.11.14
17	018	150.0	225.0	15 min	2024.11.15	2029.11.14
18	075	150.0	225.0	15 min	2024.11.15	2029.11.14
19	020	150.0	225.0	15 min	2024.11.15	2029.11.14
20	076	150.0	225.0	15 min	2024.11.15	2029.11.14

REMARKS : Pressure Test was performed according to International Standard ISO 7866:2012 and results were found satisfactory

Tested By : Abdulrahman Loay



Approved By Asjad Rafiq



Certificate of Hydro Test

Al Takamul Yard, North Rumailah South Iraq

• Phone : +964 7810009138 • www.qualitycontrol-iraq.com • E-mail: op@qualitycontrol-iraq.com

Coustmer	: Black Gold Gulf, Basra, South Iraq	Job Number	: QC-YB-240051
Description	: Refillable Seamless Steel Gas Cylinders	Certificate No.	: QC-YB-240051-13
Cylinder Type	: NITROGEN N2	Temperature	: 22 ± 2°C
Manufacturer	: SHANDONG BEE GAS ENERGY TECH CO., LTD	Humidity	: 25 ± 5 % RH
Volumetric Capacity (L)	: 40.4 ± 0.1 L	Ref. Standard	: ISO 7866:2012

No.	Serial No.	Working Pressure (Bar)	Test Pressure (Bar)	Holding Time (m)	Hydro test date	Expired date
1	023	150.0	225.0	15 min	2024.11.15	2029.11.14
2	029	150.0	225.0	15 min	2024.11.15	2029.11.14
3	055	150.0	225.0	15 min	2024.11.15	2029.11.14
4	050	150.0	225.0	15 min	2024.11.15	2029.11.14
5	072	150.0	225.0	15 min	2024.11.15	2029.11.14
6	044	150.0	225.0	15 min	2024.11.15	2029.11.14
7	014	150.0	225.0	15 min	2024.11.15	2029.11.14
8	074	150.0	225.0	15 min	2024.11.15	2029.11.14
9	028	150.0	225.0	15 min	2024.11.15	2029.11.14
10	026	150.0	225.0	15 min	2024.11.15	2029.11.14
11	082	150.0	225.0	15 min	2024.11.15	2029.11.14
12	066	150.0	225.0	15 min	2024.11.15	2029.11.14
13	002	150.0	225.0	15 min	2024.11.15	2029.11.14
14	010	150.0	225.0	15 min	2024.11.15	2029.11.14
15	045	150.0	225.0	15 min	2024.11.15	2029.11.14
16	032	150.0	225.0	15 min	2024.11.15	2029.11.14
17	073	150.0	225.0	15 min	2024.11.15	2029.11.14
18	046	150.0	225.0	15 min	2024.11.15	2029.11.14
19	022	150.0	225.0	15 min	2024.11.15	2029.11.14
20	021	150.0	225.0	15 min	2024.11.15	2029.11.14

REMARKS : Pressure Test was performed according to International Standard ISO 7866:2012 and results were found satisfactory

Tested By : Abdulrahman Loay



Approved By Asjad Rafiq



Certificate of Hydro Test

Al Takamul Yard, North Rumailah South Iraq

• Phone : +964 7810009138 • www.qualitycontrol-iraq.com • E-mail: op@qualitycontrol-iraq.com

Coustmer	: Black Gold Gulf, Basra, South Iraq	Job Number	: QC-YB-240051
Description	: Refillable Seamless Steel Gas Cylinders	Certificate No.	: QC-YB-240051-15
Cylinder Type	: NITROGEN N2	Temperature	: 22 ± 2°C
Manufacturer	: SHANDONG BEE GAS ENERGY TECH CO., LTD	Humidity	: 25 ± 5 % RH
Volumetric Capacity (L)	: 40.4 ± 0.1 L	Ref. Standard	: ISO 7866:2012

No.	Serial No.	Working Pressure (Bar)	Test Pressure (Bar)	Holding Time (m)	Hydro test date	Expired date
1	078	150.0	225.0	15 min	2024.11.12	2029.11.11
2	035	150.0	225.0	15 min	2024.11.12	2029.11.11
3	013	150.0	225.0	15 min	2024.11.12	2029.11.11
4	053	150.0	225.0	15 min	2024.11.12	2029.11.11
5	056	150.0	225.0	15 min	2024.11.12	2029.11.11
6	049	150.0	225.0	15 min	2024.11.12	2029.11.11
7	015	150.0	225.0	15 min	2024.11.12	2029.11.11
8	048	150.0	225.0	15 min	2024.11.12	2029.11.11
9	071	150.0	225.0	15 min	2024.11.12	2029.11.11
10	047	150.0	225.0	15 min	2024.11.12	2029.11.11
11	077	150.0	225.0	15 min	2024.11.12	2029.11.11
12	036	150.0	225.0	15 min	2024.11.12	2029.11.11
13	017	150.0	225.0	15 min	2024.11.12	2029.11.11
14	034	150.0	225.0	15 min	2024.11.12	2029.11.11
15	079	150.0	225.0	15 min	2024.11.12	2029.11.11
16	008	150.0	225.0	15 min	2024.11.12	2029.11.11
17	038	150.0	225.0	15 min	2024.11.12	2029.11.11
18	001	150.0	225.0	15 min	2024.11.12	2029.11.11
19	058	150.0	225.0	15 min	2024.11.12	2029.11.11
20	004	150.0	225.0	15 min	2024.11.12	2029.11.11

REMARKS : Pressure Test was performed according to International Standard ISO 7866:2012 and results were found satisfactory

Tested By : Abdulrahman Loay



Approved By Asjad Rafiq



Certificate of Hydro Test

Al Takamul Yard, North Rumailah South Iraq

• Phone : +964 7810009138 • www.qualitycontrol-iraq.com • E-mail: op@qualitycontrol-iraq.com

Coustmer	: Black Gold Gulf, Basra, South Iraq	Job Number	: QC-YB-240051
Description	: Refillable Seamless Steel Gas Cylinders	Certificate No.	: QC-YB-240051-16
Cylinder Type	: NITROGEN N2	Temperature	: 22 ± 2°C
Manufacturer	: SHANDONG BEE GAS ENERGY TECH CO., LTD	Humidity	: 25 ± 5 % RH
Volumetric Capacity (L)	: 40.4 ± 0.1 L	Ref. Standard	: ISO 7866:2012

No.	Serial No.	Working Pressure (Bar)	Test Pressure (Bar)	Holding Time (m)	Hydro test date	Expired date
1	025	150.0	225.0	15 min	2024.11.12	2029.11.11
2	041	150.0	225.0	15 min	2024.11.12	2029.11.11
3	042	150.0	225.0	15 min	2024.11.12	2029.11.11
4	030	150.0	225.0	15 min	2024.11.12	2029.11.11
5	065	150.0	225.0	15 min	2024.11.12	2029.11.11
6	067	150.0	225.0	15 min	2024.11.12	2029.11.11
7	081	150.0	225.0	15 min	2024.11.12	2029.11.11
8	060	150.0	225.0	15 min	2024.11.12	2029.11.11
9	080	150.0	225.0	15 min	2024.11.12	2029.11.11
10	007	150.0	225.0	15 min	2024.11.12	2029.11.11
11	063	150.0	225.0	15 min	2024.11.12	2029.11.11
12	005	150.0	225.0	15 min	2024.11.12	2029.11.11
13	052	150.0	225.0	15 min	2024.11.12	2029.11.11
14	043	150.0	225.0	15 min	2024.11.12	2029.11.11
15	061	150.0	225.0	15 min	2024.11.12	2029.11.11
16	039	150.0	225.0	15 min	2024.11.12	2029.11.11
17	059	150.0	225.0	15 min	2024.11.12	2029.11.11
18	051	150.0	225.0	15 min	2024.11.12	2029.11.11
19	009	150.0	225.0	15 min	2024.11.12	2029.11.11
20	024	150.0	225.0	15 min	2024.11.12	2029.11.11

REMARKS : Pressure Test was performed according to International Standard ISO 7866:2012 and results were found satisfactory

Tested By : Abdulrahman Loay



Approved By Asjad Rafiq

