

AI TAKAMUL COMPANY FOR ENGINEERING TESTS AND PROFESSIONAL SAFETY LIMITED

Basra, North Rumaila, Quality Control Yard – Iraq

Tel: +9647810009138 / +9647834964657

Email: OP@qualitycontrol-iraq.com / hany.akafi@qualitycontrol-iraq.com



16 INCH RELAY DSL SHEAVE ASSEMBLY ANNUALLY INSPECTION CERTIFICATE

Customer:	HALLIBURTON (WPS)	Date of Inspection:	01.July.2025
Location:	Burjesia Halliburton Basra -Iraq	Next Date of Inspection:	30.June.2026
Type Of Inspection:	Visual & Dimension Checks & MPI , DPI	Report No.:	QC-WPS-25-0102/67
Ref Standard:	API RP 9B / ASTM E709/ASTM E165	Document number:	D02213619
SERIAL NO:	S-3761-11	SAP NO.	11914534
Rated Capacity:	6,000 LBS	Wire Rope Diameter	0.125"
Model:	SH-A-2004	Max Line Pull	3.600 LBS

INSPECTION PROCEDURE (LIGHT WEIGHT COMPOSITE SHEAVE) MANUFACTURER: TIS

- Wash thoroughly to remove all of the dirt and mud.
- Does not direct high pressure spray onto the face of bearings to prevent water displacing of the grease.
- Make a visual inspection, check for no evidence of corrosion, cracks or fractures on the wheel frame that undermine its operational capabilities or safety. Inspect the cable groove all around the sheave wheel.
- Using the Sheave Gauge and using as reference the Sheave Groove Inspection guidelines **D02213619** determine if the groove is in specifications. If worn too much, it will begin to wear the cable unevenly. The sheave should be changed if this is the case.
- Check that the nameplate is intact and legible
- Rotate sheave freely and crack for wobble. Any excessive play could indicate a worn or damaged bearing. This must be repaired by replacing the sheave wheel, bearing assembly or the shaft.
- The maximum allowance for reduction of a product's original dimension due to wear or repair before removal from service is:
- Any crack or deformation in a component is sufficient cause to remove from service.
- Deformation in side plates, pins and axles, fitting attachment points, trunnions, etc. deformation can be cause by abusive service and / or overload and may be a cause to remove block or sheave from service.

Name of Inspector:	Signature & Stamp:	Name of person authenticating this report:	Customer Name , Signature
M.SHAHZAD AHMED		HANY ALI	ALI Talib HB48903 Date: 02-07-2025 Signature
QUALIFICATION: ASNT LEVEL II: MT & PT & VT & UT			



AI TAKAMUL COMPANY FOR ENGINEERING TESTS AND PROFESSIONAL SAFETY LIMITED

Basra, North Rumaila, Quality Control Yard – Iraq

Tel: +9647810009138 / +9647834964657

Email: OP@qualitycontrol-iraq.com / hany.akafi@qualitycontrol-iraq.com



16 INCH RELAY DSL SHEAVE ASSEMBLY ANNUALLY INSPECTION CERTIFICATE

Customer:	HALLIBURTON (WPS)	Date of Inspection:	01.July.2025
Location:	Burjesia Halliburton Basra -Iraq	Next Date of Inspection:	30.June.2026
Type Of Inspection:	Visual & Dimension Checks & MPI , DPI	Report No.:	QC-WPS-25-0102/67
Ref Standard:	API RP 9B / ASTM E709/ASTM E165	Document number:	D02213619
SERIAL NO:	S-3761-11	SAP NO.	11914534
Rated Capacity:	6,000 LBS	Wire Rope Diameter	0.125"
Model:	SH-A-2004	Max Line Pull	3.600 LBS


Depth Measurements of 16 Inch Sheaves Wheel

WIRE ROPE DIA:	ACTUAL GROOVE DEPT.	MIN ALLOWABLE GROOVE DEPT	Result
0.125" -3 .18 MM	19.45 MM	0.166" (4.21MM)	ACCEPTABLE

Radius Measurements of 16 Inch Sheaves Wheel

WIRE ROPE DIA:	ACTUAL GROOVE RADIUS.	GROOVE RADIUS MINI WORN.	GROOVE RADIUS MINI NEW.	GROOVE RADIUS MAXI.	Result
0.125" -3 .18 MM	1.683 MM	1.629 MM	1.685 MM	1.749 MM	ACCEPTABLE

SHEAVE PICTORIAL



INSPECTION RESULT

INSPECTION RESULT	RESULT
1-Visual & Dimension Checks (found free from deforms, cracks, Wear & mechanical damage)	ACCEPTABLE

Name of Inspector:	Signature & Stamp:	Name of person authenticating this report:	Customer Name , Signature
M.SHAHZAD AHMED		HANY ALI	ALI Talib HB48903 Date: 02-07-2025 Signature
QUALIFICATION: ASNT LEVEL II: MT & PT & VT & UT			



AI TAKAMUL COMPANY FOR ENGINEERING TESTS AND PROFESSIONAL SAFETY LIMITED

Basra, North Rumaila, Quality Control Yard – Iraq

Tel: +9647810009138 / +9647834964657


Email: OP@qualitycontrol-iraq.com / hany.akafi@qualitycontrol-iraq.com



16 INCH RELAY DSL SHEAVE ASSEMBLY ANNUALLY INSPECTION CERTIFICATE

Customer:	HALLIBURTON (WPS)	Date of Inspection:	01.July.2025
Location:	Burjesia Halliburton Basra -Iraq	Next Date of Inspection:	30.June.2026
Type Of Inspection:	Visual & Dimension Checks & MPI , DPI	Report No.:	QC-WPS-25-0102/67
Ref Standard:	API RP 9B / ASTM E709/ASTM E165	Document number:	D02213619
SERIAL NO:	S-3761-11	SAP NO.	11914534
Rated Capacity:	6,000 LBS	Wire Rope Diameter	0.125"
Model:	SH-A-2004	Max Line Pull	3.600 LBS

RELAY DSL SHEAVE ASSY FULL PICTORIAL



INSPECTION RESULT

RESULT

1-Visual Inspection (found free from deforms, cracks, Wear, corrosion & mechanical damage)	ACCEPTABLE
2-Magnetic Particle Inspection forgn areas free from cracks and other defects)	ACCEPTABLE
3-Dye Penetrant Inspection forgn areas free from cracks and other defects)	ACCEPTABLE

Equipment & Technical Details

Digital Lux Meter WHITE LIGHT	2722003	CAL DUE DATE	9-Oct-25	White Contrast WCP- 2	MANUFACTU RE	BATCH NO	EXPIRE DATE
AC YOKE	201504052	CAL DUE DATE	7-Oct-25		Magnaflux	230408	APRIL,2026
ASTM Test Block:	1657	CAL DUE DATE	7-Oct-25	Black Magnetic Ink 7HF	Magnaflux	230604	JUNE, 2026
COMPARATOR BLOCK	11223	CAL DUE DATE	8-Oct-25	Red Penetrant	Magnaflux	230606	June,2026
INFRARED THERMOMETER	201704125	CAL DUE DATE	7-Oct-25	Developer	Magnaflux	230608	June,2026
PENETRANT DWELL TIME:	30 minutes	DEVELOPER DWELL TIME:	15 minutes	WHITE LIGHT INTENSITY:	3640 lux	TEST PART TEMPERATURE	104 °F

Name of Inspector:	Signature & Stamp:	Name of person authenticating this report:	Customer Name , Signature
M.SHAHZAD AHMED		HANY ALI	ALI Talib HB48903 Date: 02-07-2025 Signature Halliburton
QUALIFICATION: ASNT LEVEL II: MT & PT & VT & UT			

