

HYDROTEST CERTIFICATE

Al Takamul Yard North Rumailah, Iraq

● Phone : +964 7810009138 ● www.qualitycontrol-iraq.com ● E-mail: op@qualitycontrol-iraq.com

Date of Issue: July 10, 2025

Page 1 of 1

REQUEST NUMBER	: By Mail	APPROVED BY LAB INCHARGE QC
JOB NUMBER	: QC-CAL-25258	
CERTIFICATE NUMBER	: QC-CAL-25258-27	

CUSTOMER DETAILS

Name : **Halliburton Worldwide IRAQ (TSS)**
 Location : Western Burjesia, Oil Street, District Zubair-South Iraq

EQUIPMENT IDENTIFICATION AND SPECIFICATIONS

Description : **Flexible Pressure Hose**
 Manufacturer : NA
 Model Number : NA
 Serial Number : **14150**
 Working Pressure : 15000 psi

Hose Diameter : 1/4"
 Hose Length : 180 in

Calibration Date : July 10, 2025
Calibration Due : July 9, 2026

ENVIRONMENTAL CONDITIONS DURING TEST

Ambient Temperature : 20 °C ± 2 °C
 Relative Humidity : 15 %RH ± 5 %RH

Testing Method

Client method was used to test the unit under test. Test pressure was applied on the whole assembly of unit under test and test was repeated 3 times. Each time the test pressure was sustained for a holding time mentioned in the test results.

REFERENCE EQUIPMENT USED :


DESCRIPTION	SERIAL NO.	MAKE / MODEL	CALIBRATION DATE	CALIBRATION DUE DATE
Digital Pressure Gauge	468802	AMETEK / XP2i	5 Nov, 2024	4 Nov, 2025

TEST RESULTS

Test Description	Test Pressure	Holding Time	Result			
Hydrostatic Pressure Test Test Medium Water	psi	Minutes				
	15000	15	☒	Pass	☐	Fail

On the basis of above mentioned results unit under test has been found complying with the requirements given by the :

- ☒ Customer
- ☐ Standard Method
- ☐ Manufacturer Specifications

CALIBRATED BY	REVIWED & APPROVED BY LAB INCHARGE	CLIENT
 Hussein Alaa	 LAB INCHARGE Asjad Rafiq	

This certificate is issued in accordance with the laboratory accreditation requirements as per ISO/IEC17025:2017. This certificate may not be reproduced other than in full, unless permission for the publication of an approved extract has been obtained in writing from the director of QC. It does not of itself impute to the subject of the calibration any attributes beyond those shown by the data contained herein.